

## AkzoNobel

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

## SAFETY DATA SHEET

BERGERMASTER CRAFTSMAN NUKOTE CREAM

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

GHS product identifier : BERGERMASTER CRAFTSMAN NUKOTE CREAM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Waterborne coating for interior and exterior use.

1.3. Details of the supplier of the safety data sheet

ICI DULUX (PTY) LTD NO. 1 PAINTS PLACE DICKENS ROAD UMBOGINTWINI

4126

**SOUTH AFRICA** 

e-mail address of person responsible for this SDS

: ZA.Helpline@akzonobel.com

1.4 Emergency telephone number

<u>Supplier</u>

**Telephone number**: Customer Care 0860 330 111 (Available week days from 08:00 to 16:30).

Emergency details: after hours: refer to website for MSDS.

Version : 2.01

Date of previous issue : 15-12-2022

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms :



Signal word : Warning

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

#### SECTION 2: Hazards identification

**Hazard statements** : H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

General : P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

**Prevention** : P280 - Wear protective gloves.

P273 - Avoid release to the environment.

P261 - Avoid breathing vapor.

: P362 + P364 - Take off contaminated clothing and wash it before reuse. Response

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national or international regulations.

**Hazardous ingredients** 

Supplemental label

elements

: C(M)IT/MIT(3:1)

: Not applicable.

: Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

**Annex XVII - Restrictions** on the manufacture, placing on the market and

use of certain dangerous substances, mixtures and

articles

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006. Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification : None known.

## SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Solvent naphtha (petroleum), heavy arom.	EC: 265-198-5 CAS: 64742-94-5 Index: 649-424-00-3	≤3	Asp. Tox. 1, H304	-	[1]
Titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤3	Carc. 2, H351 (inhalation)	-	[1] [*]
Naphthalene	EC: 202-049-5 CAS: 91-20-3	≤0.3	Acute Tox. 4, H302 Carc. 2, H351	ATE [Oral] = 500 mg/kg	[1] [2]

Date of issue/Date of revision : 7-6-2023 : 15-12-2022 Version : 2.01 Date of previous issue

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## **SECTION 3: Composition/information on ingredients**

	Index: 601-052-00-2		Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	
ammonia	EC: 215-647-6 CAS: 1336-21-6	≤0.3	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	STOT SE 3, H335: C ≥ 5% M [Acute] = 1	[1] [2]
C(M)IT/MIT(3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	≤0.014	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Skin Irrit. 2, H315: $0.06\% \le C < 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

Substance classified with a health or environmental hazard

- [2] Substance with a workplace exposure limit
- [\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 3/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

#### **SECTION 4: First aid measures**

#### Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

#### Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains C(M)IT/MIT(3:1). May produce an allergic reaction.

#### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 4/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion** products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 7-6-2023 : 15-12-2022 Date of previous issue Version : 2.01

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

### **SECTION 6: Accidental release measures**

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

## 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance.

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8.2 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations : Not available.
Industrial sector specific : Not available.
solutions

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### Occupational exposure limits

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 6/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Exposure limit values
<b>M</b> aphthalene	EU OEL (Europe, 1/2022). Notes: list of indicative
	occupational exposure limit values
	TWA: 10 ppm 8 hours.
	TWA: 50 mg/m³ 8 hours.
ammonia	EU OEL (Europe, 1/2022). [ammonia, anhydrous] Notes: list of
	indicative occupational exposure limit values
	TWA: 20 ppm 8 hours.
	TWA: 14 mg/m <sup>3</sup> 8 hours.
	STEL: 50 ppm 15 minutes.
	STEL: 36 mg/m³ 15 minutes.

## Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects		
Solvent naphtha (petroleum), heavy	DNEL	Long term Oral	0.03 mg/	General	Systemic		
arom.	DAIEI	 	kg bw/day	population	0		
	DNEL	Long term Dermal	0.28 mg/	General	Systemic		
	DNIEL	Long torm	kg bw/day	population	Local		
	DNEL	Long term Inhalation	0.69 mg/m <sup>3</sup>		Local		
	DNEL	Long term	0.69 mg/m <sup>3</sup>	population General	Systemic		
	DINEL	Inhalation	0.69 1119/111	population	Systernic		
	DNEL	Long term Dermal	0.95 mg/	Workers	Systemic		
	DINEL	Long term Dermai	kg bw/day	VVOIKeis	Systemic		
	DNEL	Long term	2.31 mg/m <sup>3</sup>	Workers	Local		
		Inhalation					
	DNEL	Long term	2.31 mg/m <sup>3</sup>	Workers	Systemic		
		Inhalation					
	DNEL	Short term Oral	25.6 mg/	General	Systemic		
			kg bw/day	population			
	DNEL	Short term	143.5 mg/	General	Local		
		Inhalation	m³	population			
	DNEL	Short term	160.23 mg/	Workers	Local		
		Inhalation	m³				
	DNEL	Short term	226 mg/m <sup>3</sup>	General	Systemic		
		Inhalation		population			
	DNEL	Short term	384 mg/m <sup>3</sup>	Workers	Systemic		
		Inhalation					
Naphthalene	DNEL	Long term Dermal	3.57 mg/	Workers	Systemic		
			kg bw/day				
	DNEL	Long term	25 mg/m³	Workers	Local		
		Inhalation					
	DNEL	Long term	25 mg/m³	Workers	Systemic		
		Inhalation			l		
C(M)IT/MIT(3:1)	DNEL	Long term	0.02 mg/m <sup>3</sup>	General	Local		
e of issue/Date of revision : 7-6-2023 Date of previous issue :15-12-2022 Version : 2.01 7/17							

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 7/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## **SECTION 8: Exposure controls/personal protection**

-				
	Inhalation		population	
DNEL	Long term	0.02 mg/m <sup>3</sup>	Workers	Local
	Inhalation			
DNEL	Short term	0.04 mg/m <sup>3</sup>	General	Local
	Inhalation		population	
DNEL	Short term	0.04 mg/m <sup>3</sup>	Workers	Local
	Inhalation			
DNEL	Long term Oral	0.09 mg/	General	Systemic
		kg bw/day	population	
DNEL	Short term Oral	0.11 mg/	General	Systemic
		kg bw/day	population	

#### **PNECs**

No PNECs available.

#### 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

## Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton @ or Nitrile, thickness  $\ge 0.38$  mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness  $\ge 0.12$  mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision : 7-6-2023 Date of previous issue :15-12-2022 Version : 2.01 8/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## SECTION 8: Exposure controls/personal protection

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Liquid.

Color : Various: See label.

Odor : Not available. Not available. Odor threshold Melting point/freezing point : Not available. Boiling point, initial boiling : 100°C (212°F)

point, and boiling range

**Flammability** Lower and upper explosion

limit

: Not available. : Not available.

: Not available. Flash point

**Auto-ignition temperature** 

Ingredient name	°C	°F	Method
Solvent naphtha (petroleum), heavy arom.	220 to 250	428 to 482	ASTM E 659
Polypropylene glycol 2025	305	581	EU A.15
Formaldehyde	430	806	
1,2,4-trimethylbenzene	500	932	
p-toluenesulphonic acid, containing a maximum of 5 % H2SO4	>465	>869	EU A.15
Naphthalene	526 to 587	978.8 to 1088.6	DIN 51794
m-xylene	527	980.6	

**Decomposition temperature** : Not available. Ha : 9 [DIN EN 1262]

**Viscosity** : Kinematic: 1153 mm<sup>2</sup>/s [DIN EN ISO 3219]

Solubility(ies)

Media	Result
cold water	Easily soluble [OESO (TG 105)]

Partition coefficient: n-octanol/ : Not applicable.

water

Vapor pressure

Date of issue/Date of revision : 7-6-2023 : 15-12-2022 Version : 2.01 Date of previous issue

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## **SECTION 9: Physical and chemical properties**

	Vapor Pressure at 20°C		Va	por pressur	e at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
ammonia	360.03	48				
Water	23.8	3.2				
m-xylene	6	0.8				
1,2,4-trimethylbenzene	2.25	0.3				
Formaldehyde	1	0.13				
Naphthalene	0.054	0.0072	OECD 104			
Solvent naphtha (petroleum), heavy arom.	0.02	0.0027				
C(M)IT/MIT(3:1)	0	0				
Polypropylene glycol 2025	0	0	OECD 104			
1-[(2,4-dinitrophenyl)azo] -2-naphthol	0	0				

Relative density : 1.388

**Density** : 1.388 g/cm³ [DIN EN ISO 2811-1]

: 0

Vapor density : Not available.

Particle characteristics

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10

μm

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Solvent naphtha (petroleum), heavy arom.	LDLo Oral	Rat	5 mL/kg	-

**Conclusion/Summary**: Not available.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 10/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## **SECTION 11: Toxicological information**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Naphthalene	500	N/A	N/A	N/A	N/A
C(M)IT/MIT(3:1)	100	50	N/A	N/A	0.05

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Solvent naphtha (petroleum),	Skin - Mild irritant	Rabbit	-	24 hours 500	-
heavy arom.				uL	
Titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug I	
Naphthalene	Skin - Mild irritant	Rabbit	-	495 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours	-
				0.05 MI	
ammonia	Eyes - Severe irritant	Rabbit	-	0.5 minutes	-
	-			1 mg	
	Eyes - Severe irritant	Rabbit	-	250 ug	-
C(M)IT/MIT(3:1)	Skin - Severe irritant	Human	-	0.01 %	-

Conclusion/Summary

: Not available.

**Sensitization** 

**Conclusion/Summary**: Not available.

**Mutagenicity** 

**Conclusion/Summary**: Not available.

**Carcinogenicity** 

**Conclusion/Summary**: Not available.

Reproductive toxicity

**Conclusion/Summary**: Not available.

**Teratogenicity** 

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ammonia	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Product/ingredient name	Result
Solvent naphtha (petroleum), heavy arom.	ASPIRATION HAZARD - Category 1

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 11/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## **SECTION 11: Toxicological information**

**Skin contact**: May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 12/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## **SECTION 12: Ecological information**

Product/ingredient name	Result	Species	Exposure
Maphthalene	Acute EC50 1.6 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2800 μg/l Marine water	Crustaceans - Elasmopus pectenicrus - Adult	48 hours
	Acute LC50 0.51 mg/l Fresh water	Fish - Melanotaenia fluviatilis - LARVAE	96 hours
	Acute LC50 553 μg/l Fresh water	Fish - Melanotaenia fluviatilis - LARVAE	96 hours
	Acute LC50 470 μg/l Fresh water	Fish - Melanotaenia fluviatilis - LARVAE	96 hours
	Chronic NOEC 0.5 mg/l Marine water	Crustaceans - Uca pugnax - Adult	3 weeks
	Chronic NOEC 1.5 mg/l Fresh water	Fish - Oreochromis mossambicus	60 days
ammonia	Acute LC50 37 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours

**Conclusion/Summary**: Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Solvent naphtha (petroleum),	2.8 to 6.5	99 to 5780	high
heavy arom. Naphthalene	3.4	36.5 to 168	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

**Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 13/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## **SECTION 13: Disposal considerations**

Methods of disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

: The classification of the product may meet the criteria for a hazardous waste.

**Disposal considerations** 

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11

#### **Packaging**

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** 

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	IMDG
14.1 UN number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

#### **Additional information**

**IMDG** : <u>Emergency schedules</u> Not applicable.

14.6 Special precautions for

user

: **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 14/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## SECTION 14: Transport information

14.7 Transport in bulk according to IMO instruments

: Not available.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorization

#### **Annex XIV**

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles **Other EU regulations** 

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the

product label and/or technical data sheet for further information.

**VOC for Ready-for-Use** 

**Mixture** 

: Not available.

: Not listed

: Not listed

Industrial emissions (integrated pollution

prevention and control) -

Air

**Industrial emissions** 

(integrated pollution prevention and control) -

Water

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### **Persistent Organic Pollutants**

Annex	Ingredient name	Status
Annex III	Naphthalene	Listed

#### **Seveso Directive**

This product is not controlled under the Seveso Directive.

#### **International regulations**

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

Date of issue/Date of revision : 7-6-2023 : 15-12-2022 Version : 2.01 15/17 Date of previous issue

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

## **SECTION 15: Regulatory information**

## Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Ingredient name	List name	Status
Naphthalene	POPs - Annex 3	Listed

#### 15.2 Chemical Safety

**Assessment** 

: No Chemical Safety Assessment has been carried out.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

#### Full text of abbreviated H statements

<b>⊮</b> 301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 2.01 16/17

#### BERGERMASTER CRAFTSMAN NUKOTE CREAM

#### SECTION 16: Other information

Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3

Asp. Tox. 1 Carc. 2 Eve Dam. 1 Skin Corr. 1B Skin Corr. 1C Skin Sens. 1 Skin Sens. 1A

ACUTE TOXICITY - Category 2 **ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4** 

AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 ASPIRATION HAZARD - Category 1

**CARCINOGENICITY - Category 2** 

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 1C

SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 3

Date of printing Date of issue/ Date of

Date of previous issue

revision

STOT SE 3

: 7-6-2023

: 13-6-2023

: 15-12-2022

Version : 2.01

#### Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

#### **Head Office**

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands

Date of issue/Date of revision : 7-6-2023 : 15-12-2022 Version : 2.01 17/17 Date of previous issue