



Technical Data Sheet

AkzoNobel
Tomorrow's Answers Today

Coral Acrylic Filler

Product Description

White creamy filler for internal and external surfaces of masonry and concrete plaster. Suitable to level out and correct small imperfections. It has a high consistency, filling power, excellent adherence and optimal alkali resistance. It does not need to be primed before painting.

Physicochemical Information

Colour:	White
Consistency:	7, 0 – 7, 7cm
Dry Gloss (@60°):	Not applicable
Specific Gravity:	1,712 – 1,752 g/cm ³
Solids (by volume):	47, 12 – 51, 12%
VOC (volatile organic compounds):	3, 15 g/L
Solids (by weight):	68, 96 – 72, 96%
Flash Point:	>100° C

Technical Information

Composition: Modified acrylic resin, inert pigments, coalescent, aliphatic hydrocarbons, surfactants, thickeners, no metallic microbicides and water.

Shelf life: 24 months

Packaging: 18L, 3.6L

Application data

Thinner:	Not applicable
Thinning:	Ready to use

Coverage per coat:	Over rough cast: 6m ² /coat/gallon Over mortar: 16m ² /coat/gallon
Tools:	Scraper or steel trowel
Drying time:	To touch: 30 minutes Recoat: 3 hours Final: 5 hours
Number of coats:	Normally 2 to 3 coats in thin layers, but depending on the type of surface, additional coats may be necessary.
Cleaning:	Always keep the tools clean with water.
Recommendations:	Avoid applying the paint during rainy days, temperatures below 10°C or above 40°C and air humidity around 85%.