



## Technical Data Sheet

**AkzoNobel**  
Tomorrow's Answers Today

### Coral Acrylic Texture

#### Product Description

Coral Acrylic Texture is the most practical way to obtain a textured effect on your walls since it can be applied directly on the plaster and can disguise small surface imperfections. It is offered in white and should not be left without a finishing paint on an external surface. It is possible to have decorative effects with other colours by applying it directly on the texture. It is recommended for internal and external surfaces.

#### Physicochemical Information

<b>Appearance:</b>	Matt
<b>Colour:</b>	White
<b>Consistency:</b>	7, 0 - 7,7cm
<b>Gloss (@60°):</b>	Not applicable
<b>Specific Weight:</b>	1,701 - 1,741 g/cm <sup>3</sup>
<b>Solids (by volume):</b>	45, 83 - 49, 83%
<b>VOC (volatile organic compounds):</b>	18, 97 g/L
<b>Solids (by weight):</b>	68, 38 - 72, 38%
<b>Flash Point:</b>	>100° C

#### Technical Information

**Composition:** Modified acrylic resin, inert pigments, aliphatic hydrocarbons, surfactants coalescent, thickeners, non-metallic microbicides and water.

**Shelf life:** 24 months

**Packaging:** 18L, 3.6L

<b>Application data</b>
-------------------------

**Thinner:** Water

**Thinning:** High reliefs: product ready for use. Do not thin.  
Low reliefs: dilute up to 10% with potable water.

**Number of coats:** 1 coat

**Spreading rate:** Up to 6 m<sup>2</sup>/ coat/ gallon  
It may vary according to the Irregularity of surface and / or desired effect.

**Tools:** Rubber, woolen or foam roller, steel trowel, scraper, brush, etc.

**Drying time:** To touch: 2 hours

Final: 4 hours

**Cleaning:** Wash the tools with water.

**Recommendations:** Avoid applying the paint during rainy days, with temperatures below 10°C or above 40°C and air humidity higher than 85%