



Technical Data Sheet

AkzoNobel
Tomorrow's Answers Today

Coral Wall Preparing Primer

Product Description

A clear water-based primer for internal and external surfaces of masonry, concrete and fiber cement. Specially developed to solve problems such as peeling, saponification or whitewash. Its high alkali resistance allows early priming of newly plastered walls (cured for at least 15 days). Not recommended for application on walls skimmed with gypsum (P.O.P).

Recommended Use: Internal and External Surfaces.

Physicochemical Information

Colour:	Colourless
Dry Gloss (@60°):	Not applicable
Specific Gravity:	0,989 – 1,029 g/cm ³
Solids (by volume):	8, 22 – 12, 22%
Solids (by weight):	8, 17 – 12, 17% g/L
VOC (volatile organic compounds):	2, 51 g/L
Flash Point:	>100° C

Technical Information

Composition: Modified acrylic resin, additives, non-metallic microbicides and water.

Shelf life: 36 months

Packaging: 18L, 3,6L

Application data

Thinner: Not available

Thinning: Ready for use

Number of coats: Normally 1 coat is enough, but depending on the type of surface, chosen additional coats may be necessary

Coverage per coat: Up to 55 m²/coat/gallon

Tools: Short-cut wool roller or a soft-bristled brush.

Drying time: To touch: 30 minutes

Recoat: 4 hours

Final: 4 hours

Cleaning: Always keep the tools clean with water.

Recommendations: Avoid applying the paint during rainy days, temperatures below 10°C or above 40°C and air humidity around 85%.