



## Technical Data Sheet

**AkzoNobel**  
Tomorrow's Answers Today

### Decora Coralplus

#### Product Description

Coralplus is a premium acrylic suitable for external surfaces. It is odorless up to 3 hours after application, by following the application instructions and keeping the environment ventilated.

According to a survey\*, 84.5% of clients evaluated odor intensity as weak/odorless. It has high durability, coverage and washability.

*\* Institute in charge: Perception pesquisa em Análise Sensorial Ltda.*

#### Physicochemical Information

<b>Colour:</b>	White and the Coral Tinting System
<b>Appearance:</b>	Matt
<b>Viscosity:</b>	90 - 100 KU
<b>Dry Gloss (@60°):</b>	Not applicable
<b>Specific Gravity:</b>	1,151 - 1,445 g/cm <sup>3</sup>
<b>Solids (by volume):</b>	25, 17 - 42, 77%
<b>VOC (volatile organic compounds):</b>	9, 61 g/L Solids (by weight): 33, 74 - 57, 69%
<b>Flash Point:</b>	>100° C

#### Technical Information

**Composition:** Modified acrylic resin, active and inert pigments, coalescent, thickeners, no metallic microbicides, other additives, and water.

**Expiration date:** 36 months

**Packaging:** 18L, 3,6L

<b>Application data</b>
-------------------------

**Thinner:** Water

**Thinning:** Thin product with 20% water

**Coverage per coat:** Up to 340m<sup>2</sup>/ coat / pail

**Tools:** Short-cut wool roller or a soft-bristled brush.

**Drying time:** To touch: 30 minutes

Recoat: 4 hours

Final: 4 hours

**Number of coats:** Normally 2 to 3 coats are enough, but depending on the type of surface, as well as the colour chosen, additional coats may be necessary.

**Cleaning:** Always keep the tools clean with water.

**Recommendations:** Avoid applying the paint during rainy days, temperatures below 10°C or above 40°C and air humidity around 85%.