



Technical Data Sheet

AkzoNobel
Tomorrow's Answers Today

Coral Gel for Textures (Ageing/ Pearlescent)

Product Description

The Gel for textures supplements the Coral decoration line, since using any of the available options; it is easy to customize the environment with decorative and exclusive effects. It is used for internal and external surfaces. It is to be applied on top of rustic, design, effect and acrylic textures.

Technical Information

Colour:	Available in Coral Tinting System
Viscosity:	70 - 85 KU
Dry Gloss (@60°):	Not applicable
Specific Gravity:	1,024 - 1,110 g/cm ³
Solids (by volume):	24 – 29%
VOC (volatile organic compounds):	6, 02 g/L
Solids (by weight):	27 – 33%
Flash Point:	>100° C

Technical Information

Composition: Modified acrylic resin, pigments, aliphatic hydrocarbons, surfactant, coalescent, thickeners, no metallic microbicides and water.

Shelf life: 36 months

Packaging: 3, 3 kg and 800 g

Application data

Thinner:	Not applicable
Thinning:	Ready to use
Coverage per coat:	Up to 48 m ² /coat/gallon Variation according to a surface irregularity and / or desired effect.

Tools:	Use according to the desired effect.
Drying time:	To touch: 30 minutes Final: 2 hours
Number of coats:	According to the desired effect
Cleaning:	Always keep the tools clean with water
Recommendations:	Avoid applying the paint during rainy days, temperatures below 10°C or above 40°C and air humidity around 85%.