



Technical Data Sheet

AkzoNobel
Tomorrow's Answers Today

Coral PVA Filler

Product Description

A white creamy filler for internal surfaces of masonry and concrete plaster. Suitable to level out and correct small imperfections. It has a high consistency, filling power and excellent adherence. It does not need to be primed before painting.

Physicochemical Information

Colour:	White
Consistency:	6, 0 – 6, 8 cm
Dry Gloss (@60°):	Not applicable
Specific Gravity:	1,702 – 1,742 g/cm ³
Solids (by volume):	39, 87 – 43, 87%
Solids (by weight):	64, 95 – 68, 95%
VOC (volatile organic compounds):	3, 15 g/l
Flash Point:	>100° C

Technical Information

Composition: Modified acrylic resin, mineral loads, aliphatic compounds, thickeners, no metallic microbicides and water.

Shelf life: 24 months

Packaging: 3.6L / Gallon and 18L / Pail

Application data

Thinner: N/A

Thinning: Product ready for use

Spreading Rate: Over roughcast: Up to 6 m²/coat/gallon

Over mortar: Up to 16 m²/coat/gallon

Tools: Scraper or steel trowel

Number of coats: Apply 2 to 3 coats in thin layers, but depending on the type of surface, additional coats may be necessary

Cleaning: Always keep the tools clean with water.

Drying time: To touch: 30 minutes

Recoat: 3 hours

Final: 5 hours

Recommendations: Avoid applying the paint during rainy days, temperatures below 10°C or above 40°C and air humidity around 85%.