



Technical Data Sheet

AkzoNobel
Tomorrow's Answers Today

Coral Wood Filler

Product Description

White wood filler is used for leveling and correcting imperfections on external and internal wooden surfaces. Its formula allows for easy application and has high filling power. It has great adherence.

Physicochemical Information

Colour:	White
Consistency:	7, 0 – 8, 0 cm
Dry Gloss (@60°):	Not applicable
Specific Gravity:	1,643 - 1,683 g/cm ³
Solids (by volume):	44, 27 – 48, 28%
Solids (by weight):	66, 76 – 70, 76%
VOC (volatile organic compounds):	54, 52 g/L
Flash Point:	>100° C

Technical Information

Composition: Modified acrylic emulsion, inert pigments, coalescent, thickeners, surfactants no metallic microbicides and water.

Shelf life: 24 months

Packaging: 3.6L gallon and 1 litre

Application data

Thinner:	Ready for use.
Thinning:	N/A
Coverage per coat:	15 m ² /coat/gallon

Tools: Scraper or steel trowel

Drying time: To touch: 30 minutes

Recoat: 3 hours

Final: 6 hours

Number of coats: Normally 1 coats are enough, but depending on the type of surface, additional coats may be necessary.

Cleaning: Always keep the tools clean with water

Recommendations: Avoid applying the paint during rainy days, temperatures below 10°C or above 40°C and air humidity around 85%.