



## Technical Data Sheet

**AkzoNobel**  
Tomorrow's Answers Today

### Coralatex Super-Spreading

#### Product Description

Coralatex Super-Spreading is a premium acrylic paint with a matt finish and ultra-high spreading rate. Its formula now contains high performance UV resistant pigments that make the colours last longer on external surfaces without fading.

Recommended Use: Internal and external walls, adhering to different masonry surfaces

#### Physicochemical Information

<b>Colour:</b>	31 Ready Mixed colours Also available in Coral Tinting System (Pastel colours only)
<b>Appearance:</b>	Matt.
<b>Viscosity:</b>	110 - 115 KU
<b>Dry Gloss (@60°):</b>	Not applicable
<b>Specific Gravity:</b>	1,141 – 1,356 g/cm <sup>3</sup>
<b>Solids (by volume):</b>	25, 0 – 40, 0%
<b>Solids (by weight):</b>	32, 85 – 50, 17%
<b>VOC (volatile organic compounds):</b>	11, 50 g/L
<b>Flash Point:</b>	>100° C

#### Technical Information

**Composition:** Modified acrylic resin, active and inert pigments, surfactants, coalescent, thickeners, no metallic microbicides, other additives, and water.

**Shelf life:** 36 months

**Packaging:** 18L, 3,6L 900mL

<b>Application data</b>
-------------------------

**Thinner:** Water

**Thinning:** Minimum 50% and maximum 80% with clean water.

**Coverage per coat:** 375m<sup>2</sup> / coat / pail

**Tools:** Short-cut wool roller or a soft-bristled brush.

**Drying time:** To touch: 30 minutes

Recoat: 4 hours

Final: 4 hours

**Number of coats:** Normally 2 to 3 coats are enough, but depending on the type of surface, as well as the colour chosen additional coats, may be necessary.

**Cleaning:** Always keep the tools clean with water

**Recommendations:** Avoid applying the paint during rainy days, temperatures below 10°C or above.