



## Technical Data Sheet

**AkzoNobel**  
Tomorrow's Answers Today

### Sparlack Stain plus Water-Based Natural Balance Interior

#### Product Description

Sparlack Stain plus Water-Based is a wood protector that forms a rain-resistant film 30 minutes after application. It also contains sunscreen. It is easy to apply because it is ready to use. It is fast-drying and has a great spreading rate, providing a very nice satin finishing. Indicated for internal surfaces and any type of industrialized wood such as: such as doors, windows, decks and garden furniture.

#### Physicochemical Information

<b>Appearance:</b>	Satin
<b>Colour:</b>	Natural
<b>Viscosity (CP4):</b>	27 - 33 seg
<b>Dry Gloss (@60°):</b>	20 - 30 UB
<b>Specific Gravity:</b>	1,012 - 1,052 g/cm <sup>3</sup>
<b>Solids (by volume):</b>	16, 73 - 20, 73%
<b>Solids (by weight):</b>	19, 39 - 23, 39%
<b>VOC (volatile organic compounds):</b>	8, 73 g/L
<b>Flash Point:</b>	> 100° C

#### Technical Information

**Composition:** product based on acrylic co-polymer dispersion, UV absorbers transparent pigments, non-metallic biocides, matting agent, additives and water.

**Expiration date:** 24 months

**Packaging:** 3,6L, 900 mL

## Application data

<b>Thinner:</b>	Not applicable
<b>Thinning:</b>	Do not thin, it is ready to use.
<b>Coverage per coat:</b>	Up to 22.5 m <sup>2</sup> / coat / 0.9L
<b>Number of coats:</b>	2 to 3 coats with intervals of 4 hours between them
<b>Tools:</b>	Use soft-bristled brush, foam roller, short-cut wool roller for epoxy.
<b>Drying time:</b>	To touch 3 hours Recoat: 4 hours Final: 5 hours
<b>Cleaning:</b>	Always keep the tools clean with water.
<b>Recommendations:</b>	Avoid applying the paint during rainy days, temperatures below 10°C or above 40°C and air humidity around 85%.