

Description

Ultra resistant protective floor coverings rolls.
A cost-effective solution to protect your floor from foot traffic and light weights:

- (1) Transparent wear layer
- (2) Decorated compact non-woven impregnation
- (3) Calendred sheet + coated non woven glas fiber



PROPERTIES

STANDARDS

TOUCHDOWN

DECLARATION OF PERFORMANCE

0120-013-DoP-2021-02

CLASSIFICATION

Type of flooring	EN 14041	Compact vinyl floorcoverings
------------------	----------	------------------------------

TECHNICAL CHARACTERISTICS

Total thickness	ISO 24346 (EN 428)	1.45mm
Total weight	ISO 23997 (EN 430)	2.2kg/m²
Width	ISO 24341 (EN 426)	2m
Length	ISO 24341 (EN 426)	27lm

TECHNICAL PERFORMANCES

Static indentation	EN ISO 10874	0.10mm
Dimensional stability	EN 434	<0.1%
Reaction to fire	EN 13501-1	Cfl-s1*
Impact sound reduction	ISO 140/8 NF EN ISO 717/2	lw=2dB
Electrical properties	EN 1081	R1 > 10 ⁹ ohms
Antistatic properties	EN 1815	<2kV
Formaldehyde	EN 717-1 EN 727-2	No formaldehyde
Pentachlorophenol	EN 12673	No pentachlorophenol

Available colours



* on Cfl and Bfl support.
Installation and maintenance guides available on request

Technical data in force as from the date of publication (04/2022).

The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement.
For more detailed technical information, please contact Tarkett.

Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.