Delphis A wonRoll Company

SAFETY DATA SHEET

Issue Date No data available Revision Date 28-Apr-2015 REVISION NUMBER: 5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name HI THERM BC-346-A

Other means of identification

Product Code BC-346-A Synonyms None

Recommended use of the chemical and restrictions on use
Recommended Use
No information available.
Uses advised against
No information available

Details of the supplier of the safety data sheet MANUFACTURED BY:
JOHN C. DOLPH, a Von Roll Company
320 New Road, MONMOUTH JUNCTION, NJ 08852

BUSINESS: (732) 329-2333 EMERGENCY: (518) 395-3310

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

ACUTE TOXICITY - DERMAL	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

	Emergency Overview
Danger	

Page: 1/12

Hazard statements

Harmful in contact with skin

Harmful if inhaled

Causes skin irritation

May cause an allergic skin reaction

May cause genetic defects

May cause cancer

Suspected of damaging fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor



Appearance No information available

PHYSICAL STATE Liquid

ODOR No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/ .? /equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific measures (see .? on this label)

Specific treatment (see .? on this label)

Call a POISON CENTER or doctor/physician if you feel unwell

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

Toxicity: Not determined

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	CAS No.	APPROX. WEIGHT PERCENT	TRADE SECRET
Solvent, Naphtha, Light Aromatic 64742-95-6	64742-95-6	30 - 60	
Xylene (Mixed Isomers) 1330-20-7	1330-20-7	10 - 30	
Solvent, Naphtha, Heavy Aromatic 64742-94-5	64742-94-5	1 - 5	
Ethyl Benzene 100-41-4	100-41-4	1 - 5	
Triphenyl Phosphite 101-02-0	101-02-0	0.1 - 1	
p-tert-Butyl-Phenol 98-54-4	98-54-4	0.1 - 1	
Formaldehyde 50-00-0	50-00-0	0.1 - 1	
Bisphenol A 80-05-7	80-05-7	0.1 - 1	

4. FIRST AID MEASURES

First aid measures

EYE CONTACTRinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

SKIN CONTACT Wash skin with soap and water.

Inhalation Remove to fresh air.

INGESTION Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Special Hazards:

None Known.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materialsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	ACGIH TLV	OSHA PEL-TWA	NIOSH IDLH
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-
Xylene (Mixed Isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	100	-
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-
Ethyl Benzene 100-41-4	TWA: 20 ppm	100	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³
Triphenyl Phosphite 101-02-0	-	-	-
p-tert-Butyl-Phenol 98-54-4	-	-	-
Formaldehyde 50-00-0	Ceiling: 0.3 ppm	0.75	IDLH: 20 ppm Ceiling: 0.1 ppm 15 min TWA: 0.016 ppm
Bisphenol A 80-05-7	-	-	-

Appropriate engineering controls

ENGINEERING CONTROLS: Exhaust ventilation.

Eyewash stations.

Use in a well ventilated area.

Individual protection measures, such as personal protective equipment

Von Roll recommends evaluation and selection of appropriate engineering controls (such as ventilation and eyewash/safety shower) as well as appropriate personal protective equipment (such as respiratory protection, protective gloves, eye protection) for safely handling this material. The following guidelines should be considered in this process.

EYE PROTECTION: Splash Goggles.

GLOVES: Rubber gloves. Nitrile gloves.

VENTILATION: Use only in well ventilated area. Localized mechanical ventilation.

RESPIRATORY PROTECTION: Use in a well ventilated area. Use approved NIOSH respiratory protection if TLV exceeded,

or over exposure is likely.

OTHER PERSONAL Rubber apron or other chemical-resistant apron.

PROTECTION DATA:

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

PHYSICAL STATE Liquid

AppearanceNo information availableODOR:HYDROCARBONDESCRIPTION:AMBERODOR THRESHOLDUNKNOWN

(PPM):

PROPERTIES Values Remarks • Method

pH No information availableMelting point/freezing point No information available

Boiling point / boiling range 85 °C / 185 °F Flash point 12 °C / 54 °F

EVAPORATION RATEFlammability (solid, gas)
No information available
No information available

Flammability Limit in Air

Upper flammability limit: 11.7 Lower flammability limit: 0.6

VAPOR PRESSURE No information available VAPOR DENSITY No information available

SPECIFIC GRAVITY 0.94

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available No information available Kinematic viscosity **Dvnamic viscosity** No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening pointNo information availableDENSITYNo information availableBulk densityNo information available

10. STABILITY AND REACTIVITY

REACTIVITY

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

CONDITIONS TO AVOID

Keep away from heat, sparks and flame. Avoid any source of ignition.

Incompatible materials

Contact with oxidizing agents. Avoid halogens.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide. Toxic metal fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

PRODUCT INFORMATION No data available

Inhalation No data available.

EYE CONTACT No data available.

SKIN CONTACT No data available.

INGESTION No data available.

HAZADDOUG DDODUGT	Oral LD50	Dermal LD50	Inhalation LC50
HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER			
Solvent, Naphtha, Light Aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Xylene (Mixed Isomers) 1330-20-7	= 3500 mg/kg (Rat) = 4820 mg/kg (Rat)	> 4350 mg/kg(Rabbit)> 1700 mg/kg(Rabbit)> 2000 mg/kg(Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h > 5.04 mg/L (Rat) 4 h
Solvent, Naphtha, Heavy Aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg(Rabbit)	> 590 mg/m³ (Rat) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat) = 4820 mg/kg (Rat)	= 15400 mg/kg (Rabbit) > 2000 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h > 5.04 mg/L (Rat)4 h
Triphenyl Phosphite 101-02-0	= 444 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 6.7 mg/L (Rat) 1 h
p-tert-Butyl-Phenol 98-54-4	= 2990 mg/kg (Rat)	= 2318 mg/kg (Rabbit)	-
Formaldehyde 50-00-0	= 600 mg/kg(Rat)	= 270 mg/kg (Rabbit)	= 0.578 mg/L (Rat) 4 h
Bisphenol A 80-05-7	= 3300 mg/kg (Rat)	= 3 mL/kg (Rabbit)	> 0.17 mg/L (Rat)6 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available. **Germ cell mutagenicity** No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	ACGIH	IARC	NTP	OSHA
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	<u>-</u>	-
Xylene (Mixed Isomers) 1330-20-7	-	Group 3	-	-
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-	-
Ethyl Benzene 100-41-4	А3	Group 2B	-	Х
Triphenyl Phosphite 101-02-0	-	-	-	-
p-tert-Butyl-Phenol 98-54-4	-	-	-	-
Formaldehyde 50-00-0	A2	Group 1	Known	X
Bisphenol A 80-05-7	-	-	-	-

Reproductive toxicity
STOT - single exposure
Aspiration hazard
No information available.
No information available.

Numerical measures of toxicity - PRODUCT INFORMATION

Toxicity: Not determined

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 5745 mg/kg

 ATEmix (dermal)
 1584 mg/kg mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

50.709% of the mixture consists of components(s) of unknown hazards to the aquatic environment

	Acute Algae Toxicity:	Acute Fish Toxicity:	Crustacea
HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER			
Solvent, Naphtha, Light Aromatic 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
Xylene (Mixed Isomers) 1330-20-7	11: 72 h Pseudokirchneriella subcapitata mg/L EC50	13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48 h water flea mg/L EC50

	T	T .=	
Solvent, Naphtha, Heavy Aromatic 64742-94-5	2.5: 72 h Skeletonema costatum mg/L EC50	1740: 96 h Lepomis macrochirus mg/L LC50 static 19: 96 h Pimephales promelas mg/L LC50	0.95: 48 h Daphnia magna mg/L EC50
		static 2.34: 96 h Oncorhynchus	
		mykiss mg/L LC50 41: 96 h	
		Pimephales promelas mg/L LC50	
		45: 96 h Pimephales promelas mg/L LC50 flow-through	
Ethyl Benzene	1.7 - 7.6: 96 h Pseudokirchneriella		1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 static 2.6 -	mykiss mg/L LC50 static 7.55 - 11:	EC50
100-41-4	11.3: 72 h Pseudokirchneriella	96 h Pimephales promelas mg/L	LC30
	subcapitata mg/L EC50 static 11: 72	LC50 flow-through 9.1 - 15.6: 96 h	
	h Pseudokirchneriella subcapitata	Pimephales promelas mg/L LC50	
	mg/L EC50 4.6: 72 h	static 32: 96 h Lepomis macrochirus	
	Pseudokirchneriella subcapitata	mg/L LC50 static 4.2: 96 h	
	mg/L EC50 438: 96 h	Oncorhynchus mykiss mg/L LC50	
	Pseudokirchneriella subcapitata	semi-static 9.6: 96 h Poecilia	
	mg/L EC50	reticulata mg/L LC50 static	
Triphenyl Phosphite 101-02-0	-	-	-
p-tert-Butyl-Phenol 98-54-4	11.2: 72 h Desmodesmus subspicatus mg/L EC50	4.71 - 5.62: 96 h Pimephales promelas mg/L LC50 flow-through 6.9: 96 h Cyprinus carpio mg/L LC50 static	3.4 - 4.5: 48 h Daphnia magna mg/L EC50 Static 3.9: 48 h Daphnia magna mg/L EC50
Formaldehyde 50-00-0	-	0.032 - 0.226: 96 h Oncorhynchus mykiss mL/L LC50 flow-through 100 - 136: 96 h Oncorhynchus mykiss mg/L LC50 static 22.6 - 25.7: 96 h Pimephales promelas mg/L LC50 flow-through 23.2 - 29.7: 96 h Pimephales promelas mg/L LC50 static 1510: 96 h Lepomis macrochirus µg/L LC50 static 41: 96 h Brachydanio rerio mg/L LC50 static	11.3 - 18: 48 h Daphnia magna mg/L EC50 Static 2: 48 h Daphnia magna mg/L LC50
Bisphenol A 80-05-7	2.5: 96 h Pseudokirchneriella subcapitata mg/L EC50	3.6 - 5.4: 96 h Pimephales promelas mg/L LC50 flow-through 4.0 - 5.5: 96 h Pimephales promelas mg/L LC50 static 4: 96 h Oncorhynchus mykiss mg/L LC50 9.9: 96 h Brachydanio rerio mg/L LC50 static	9.2 - 11.4: 48 h Daphnia magna mg/L EC50 Static 10.2: 48 h Daphnia magna mg/L EC50 3.9: 48 h Daphnia magna mg/L EC50

Persistence and degradability No information available.

Bioaccumulation

No information available.

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	Partition coefficient
Solvent, Naphtha, Light Aromatic 64742-95-6	-
Xylene (Mixed Isomers) 1330-20-7	2.77 - 3.15
Solvent, Naphtha, Heavy Aromatic 64742-94-5	2.9 - 6.1
Ethyl Benzene 100-41-4	3.118
Triphenyl Phosphite 101-02-0	4.98
p-tert-Butyl-Phenol 98-54-4	2.44
Formaldehyde 50-00-0	0.35
Bisphenol A 80-05-7	2.2

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

EPA HAZARDOUS WASTE DISPOSAL CODE: D001, RQ = 100 lb / 45.4 kg.

OODE.	RCRA Classification:	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER				
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-	-
Xylene (Mixed Isomers) 1330-20-7	-	Included in waste stream: F039	-	U239
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-	-
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-
Triphenyl Phosphite 101-02-0	-	-	-	-
p-tert-Butyl-Phenol 98-54-4	-	-	-	-
Formaldehyde 50-00-0	U122	Included in waste streams: K009, K010, K038, K040, K156, K157	-	U122
Bisphenol A 80-05-7	-	-	-	-

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-	-
Xylene (Mixed Isomers) 1330-20-7	-	-	-	-
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-	-
Ethyl Benzene 100-41-4	-	-	-	-
Triphenyl Phosphite 101-02-0	-	-	-	-
p-tert-Butyl-Phenol 98-54-4	-	-	-	-
Formaldehyde 50-00-0	-	-	-	-
Bisphenol A 80-05-7	-	-	-	-

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	California Hazardous Waste Status
Solvent, Naphtha, Light Aromatic 64742-95-6	-
Xylene (Mixed Isomers) 1330-20-7	Toxic Ignitable
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-

Page: 9/12

Ethyl Benzene 100-41-4	Toxic Ignitable
Triphenyl Phosphite 101-02-0	-
p-tert-Butyl-Phenol 98-54-4	-
Formaldehyde 50-00-0	Toxic Ignitable
Bisphenol A 80-05-7	-

14. TRANSPORT INFORMATION

DOT SHIPPING NAME: PAINT DOT HAZARD CLASS: 3
DOT PACKING GROUP: PG II

DOT LABEL(S): FLAMMABLE LIQUID

UN/NA NUMBER: UN1263

PLACARDS: FLAMMABLE LIQUID

ICAO/IATA: 3, II

MARINE POLLUTANT: NONE NMFC CLASSIFICATION: CLASS 55

15. REGULATORY INFORMATION

International Inventories

Complies **TSCA** Complies **DSL/NDSL** Does not comply **EINECS/ELINCS ENCS** Does not comply Does not comply **IECSC KECL** Complies **PICCS** Does not comply **AICS** Does not comply

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

ACUTE HEALTH HAZARD No
FIRE HAZARD No
Sudden release of pressure hazard No
REACTIVE HAZARD No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-	-
Xylene (Mixed Isomers) 1330-20-7	100 lb	-	-	Х
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-	-
Ethyl Benzene 100-41-4	1000 lb	X	X	Х
Triphenyl Phosphite 101-02-0	-	-	-	-
p-tert-Butyl-Phenol 98-54-4	-	-	-	-
Formaldehyde 50-00-0	100 lb	-	-	Х
Bisphenol A 80-05-7	-	-	-	-

CERCLA

	Hazardous Substances RQs	CERCLA/SARA RQ
HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER		
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-
Xylene (Mixed Isomers) 1330-20-7	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-
Ethyl Benzene 100-41-4	1000 lb	RQ 1000 lb final RQ RQ 454 kg final RQ
Triphenyl Phosphite 101-02-0	-	-
p-tert-Butyl-Phenol 98-54-4	-	-
Formaldehyde 50-00-0	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ
Bisphenol A 80-05-7	-	-

US State Regulations

CALIFORNIA PROPOSITION 65

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	CALIFORNIA PROPOSITION 65
Solvent, Naphtha, Light Aromatic 64742-95-6	-
Xylene (Mixed Isomers) 1330-20-7	-
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-
Ethyl Benzene 100-41-4	Carcinogen
Triphenyl Phosphite 101-02-0	-
p-tert-Butyl-Phenol 98-54-4	-
Formaldehyde 50-00-0	Carcinogen
Bisphenol A 80-05-7	-

Page: 11/12

U.S. State Right-to-Know Regulations

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	New Jersey Right-to-Know List:	MA Right to Know Law:	Pennsylvania Right to Know List
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-
Xylene (Mixed Isomers) 1330-20-7	Х	Х	X
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-
Ethyl Benzene 100-41-4	Х	Х	X
Triphenyl Phosphite 101-02-0	-	-	-
p-tert-Butyl-Phenol 98-54-4	-	-	-
Formaldehyde 50-00-0	Х	Х	X
Bisphenol A 80-05-7	Х	Х	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not Applicable

16. OTHER INFORMATION

NFPA RATING: HEALTH 3, FLAMMABILITY 3, INSTABILITY 1

HMIS CLASSIFICATION: HEALTH *3, FLAMMABILITY 3, PHYSICAL HAZARD 1

Prepared By Santino M. Cardella Revision Date Search 28-Apr-2015

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

END OF MSDS