

Insulthane® EDGE 600

Two-Component Low-Pressure Foam Kit

INSULTHANE® EDGE 2K 600 is a two-component, low-pressure spray polyurethane foam kit designed for fast, simple touch-ups on the jobsite. This medium-density system is ideal for small service calls, post-inspection corrections, and precision detailing. It delivers reliable performance in a compact, ready-to-use format.

For professional use only.

FEATURES

Compact & Portable

Precise Sealing

Versatile Performance

Efficient Yield



Insulthane® EDGE

Insulthane® EDGE 2K 600 is a practical solution for small-scale spray foam applications that don't require mobilizing a full rig. Designed for jobsite flexibility, this low-pressure kit provides reliable performance for sealing, detailing, and corrective work. It's well-suited for touch-ups after trimming, post-inspection fixes, or projects in hard-to-reach areas.

TECHNICAL SPECS

Insulthane® EDGE 2K 600

R-VALUE 6.1 at 1" (Aged 180 Days)

DENSITY Free Rise: 1.75 lbs/ft³ (28.0 kg/m³) In Place: 2.11 lbs/ft³ (35.2 kg/m³)

YIELD 605 ft² (56.2 m²)

(BOARD FT) (Based on free-rise density)

TACK-FREE 30-60 seconds

CUTTABLE Approx. 10 minutes

CELL Closed-Cell > 90%

CAN/ULC S102 at 4" beads

FIRE RATING Flame Spread: 20

Smoke Developed: 60

APPROVALS/ STANDARDS

CCMC #14933-L

SHELF LIFE 24 months





MEET THE FAMILY

The Insulthane® EDGE line includes a collection of high-performance foam sealants and accessories designed to support spray foam insulation work at every stage. Discover the full lineup built to make your job easier.

elastochem.com/insulthane-edge

