

## SAFETY DATA SHEET

### Epoxy Resin ER2225, Part A

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

##### **1.1. Product identifier**

**Product name** Epoxy Resin ER2225, Part A

**Product number** ER2225A, EER2225RP250G, EER2225K5K, ZE

##### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Resin.

**Uses advised against** No specific uses advised against are identified.

##### **1.3. Details of the supplier of the safety data sheet**

###### **Supplier**

ELECTROLUBE. A division of HK WENTWORTH LTD  
 ASHBY PARK, COALFIELD WAY,  
 ASHBY DE LA ZOUCH, LEICESTERSHIRE LE65 1JR  
 UNITED KINGDOM  
 +44 (0)1530 419600  
 +44 (0)1530 416640  
 info@hkw.co.uk

##### **1.4. Emergency telephone number**

**Emergency telephone** +44 1865 407333

#### **SECTION 2: Hazards identification**

##### **2.1. Classification of the substance or mixture**

###### **Classification (EC 1272/2008)**


**Physical hazards** Not Classified

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

**Environmental hazards** Aquatic Chronic 2 - H411

##### **2.2. Label elements**

###### **Pictogram**



**Signal word** Warning

**Hazard statements** H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

## Epoxy Resin ER2225, Part A

<b>Precautionary statements</b>	P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.
<b>Contains</b>	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) , 1,6-bis(2,3-epoxypropoxy)hexane, formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
<b>Supplementary precautionary statements</b>	P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

<b>Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)</b>	<b>30-60%</b>
CAS number: 25068-38-6	EC number: 500-033-5
REACH registration number: 01-2119456619-26-XXXX	
<b>Classification</b>	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
<b>1,6-bis(2,3-epoxypropoxy)hexane</b>	<b>1-5%</b>
CAS number: 16096-31-4	REACH registration number: 01-2119463471-41-XXXX
<b>Classification</b>	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	
<b>2-Methoxy-1-methylethyl acetate</b>	<b>&lt;1%</b>
CAS number: 108-65-6	EC number: 203-603-9
REACH registration number: 01-2119475791-29-XXXX	
<b>Classification</b>	
Flam. Liq. 3 - H226	

## Epoxy Resin ER2225, Part A

<b>formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol</b>		<b>&lt;1%</b>
CAS number: 9003-36-5	EC number: 500-006-8	REACH registration number: 01-2119454392-40-0000
<b>Classification</b>		
Skin Irrit. 2 - H315		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		
<b>Cyclohexanone</b>		<b>&lt;1%</b>
CAS number: 108-94-1	EC number: 203-631-1	REACH registration number: 01-2119453616-35-XXXX
<b>Classification</b>		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H332		

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin contact</b>	It is important to remove the substance from the skin immediately. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognised skin cleansing agent. Get medical attention if symptoms are severe or persist after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

#### 4.2. Most important symptoms and effects, both acute and delayed

## Epoxy Resin ER2225, Part A

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged inhalation of high concentrations may damage respiratory system.
<b>Ingestion</b>	May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.
<b>Skin contact</b>	May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.
<b>Eye contact</b>	Irritating to eyes.

### **4.3. Indication of any immediate medical attention and special treatment needed**

<b>Notes for the doctor</b>	Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.
-----------------------------	--

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

<b>Suitable extinguishing media</b>	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### **5.2. Special hazards arising from the substance or mixture**

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

### **5.3. Advice for firefighters**

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid contact with skin and eyes.
-----------------------------	---

### **6.2. Environmental precautions**

<b>Environmental precautions</b>	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).
----------------------------------	--

### **6.3. Methods and material for containment and cleaning up**

## Epoxy Resin ER2225, Part A

<b>Methods for cleaning up</b>	<p>Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.</p>
--------------------------------	---

### **6.4. Reference to other sections**

<b>Reference to other sections</b>	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	---

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

<b>Usage precautions</b>	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.
<b>Advice on general occupational hygiene</b>	Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### **7.2. Conditions for safe storage, including any incompatibilities**

<b>Storage precautions</b>	Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.
<b>Storage class</b>	Miscellaneous hazardous material storage.

### **7.3. Specific end use(s)**

<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

## **SECTION 8: Exposure Controls/personal protection**

### **8.1. Control parameters**

#### **Occupational exposure limits**

##### **2-Methoxy-1-methylethyl acetate**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m<sup>3</sup>

Sk

##### **Cyclohexanone**

## Epoxy Resin ER2225, Part A

Long-term exposure limit (8-hour TWA): WEL 10 ppm 41 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 20 ppm 82 mg/m<sup>3</sup>

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### **8.2. Exposure controls**

#### **Protective equipment**



#### **Appropriate engineering controls**

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

#### **Eye/face protection**

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### **Hand protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

#### **Other skin and body protection**

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

#### **Hygiene measures**

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

#### **Respiratory protection**

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

#### **Environmental exposure controls**

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and Chemical Properties**

## Epoxy Resin ER2225, Part A

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Odour</b>	Characteristic.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	Not available.
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Other flammability</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Not available.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.

### 9.2. Other information

#### **SECTION 10: Stability and reactivity**

##### 10.1. Reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
-------------------	--

##### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
------------------	---

##### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	No potentially hazardous reactions known.
---	---

##### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	There are no known conditions that are likely to result in a hazardous situation.
----------------------------	---

##### 10.5. Incompatible materials

<b>Materials to avoid</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
---------------------------	--

## Epoxy Resin ER2225, Part A

### **10.6. Hazardous decomposition products**

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

### **SECTION 11: Toxicological information**

#### **11.1. Information on toxicological effects**

##### **Acute toxicity - oral**

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### **Acute toxicity - dermal**

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### **Acute toxicity - inhalation**

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

##### **Skin corrosion/irritation**

**Animal data** Irritating.

##### **Serious eye damage/irritation**

**Serious eye damage/irritation** Causes serious eye irritation.

##### **Respiratory sensitisation**

**Respiratory sensitisation** Based on available data the classification criteria are not met.

##### **Skin sensitisation**

**Skin sensitisation** May cause skin sensitisation or allergic reactions in sensitive individuals.

##### **Germ cell mutagenicity**

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

##### **Carcinogenicity**

**Carcinogenicity** Based on available data the classification criteria are not met.

**IARC carcinogenicity** Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.

##### **Reproductive toxicity**

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

##### **Specific target organ toxicity - single exposure**

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.

##### **Specific target organ toxicity - repeated exposure**

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

##### **Aspiration hazard**

**Aspiration hazard** Based on available data the classification criteria are not met.

##### **General information**

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

##### **Inhalation**

Prolonged inhalation of high concentrations may damage respiratory system.

##### **Ingestion**

May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.

## Epoxy Resin ER2225, Part A

<b>Skin contact</b>	May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.
<b>Eye contact</b>	Irritating to eyes.
<b>Route of entry</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target organs</b>	No specific target organs known.
<b>Medical considerations</b>	Skin disorders and allergies.

**Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)**

**Skin corrosion/irritation**

**Skin corrosion/irritation**      Irritating to skin.

**Serious eye damage/irritation**

**Serious eye damage/irritation**      Irritation of eyes is assumed.

**Carcinogenicity**

**Carcinogenicity**      No evidence of carcinogenicity in animal studies.

**1,6-bis(2,3-epoxypropoxy)hexane**

**Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)**      3,741.0

**Species**      Rat

**ATE oral (mg/kg)**      3,741.0

**oxirane, mono[(C12-14-alkyloxy)methyl] derivs.**

**Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)**      17,100.0

**Species**      Rat

**ATE oral (mg/kg)**      17,100.0

**Cyclohexanone**

**Acute toxicity - inhalation**

**ATE inhalation (gases ppm)**      4,500.0

**ATE inhalation (vapours mg/l)**      11.0

**ATE inhalation (dusts/mists mg/l)**      1.5

**Carcinogenicity**

**IARC carcinogenicity**      IARC Group 3 Not classifiable as to its carcinogenicity to humans.

**SECTION 12: Ecological Information**

## Epoxy Resin ER2225, Part A

### 12.1. Toxicity

**Toxicity** Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

#### Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 1.3 mg/l, *Onchorhynchus mykiss* (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 2.1 mg/l, *Daphnia magna*

**Chronic toxicity - aquatic invertebrates** NOEC, 21 days: 0.3 mg/l, *Daphnia magna*

#### Cyclohexanone

**Acute toxicity - fish** Data lacking.

### 12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

#### Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

**Persistence and degradability** Not readily biodegradable.

#### Cyclohexanone

**Biodegradation** Data lacking.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

#### Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

**Bioaccumulative potential** Bioaccumulation is unlikely.

**Partition coefficient** log Kow: 2.64-3.78

#### Cyclohexanone

**Bioaccumulative potential** Data lacking.

### 12.4. Mobility in soil

**Mobility** No data available.

#### Cyclohexanone

**Mobility** No data available.

### 12.5. Results of PBT and vPvB assessment

#### Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

## Epoxy Resin ER2225, Part A

**Results of PBT and vPvB** This product does not contain any substances classified as PBT or vPvB. assessment

### Cyclohexanone

**Results of PBT and vPvB** This product does not contain any substances classified as PBT or vPvB. assessment

### **12.6. Other adverse effects**

**Other adverse effects** None known.

### Cyclohexanone

**Other adverse effects** Not known.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

**General information** The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

**Disposal methods** Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

## **SECTION 14: Transport information**

**General** For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

### **14.1. UN number**

<b>UN No. (ADR/RID)</b>	3082
<b>UN No. (IMDG)</b>	3082
<b>UN No. (ICAO)</b>	3082
<b>UN No. (ADN)</b>	3082

### **14.2. UN proper shipping name**

<b>Proper shipping name (ADR/RID)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) , Solvent naphtha (petroleum), light arom.)
<b>Proper shipping name (IMDG)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) , Solvent naphtha (petroleum), light arom.)


## Epoxy Resin ER2225, Part A

<b>Proper shipping name (ICAO)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700) , Solvent naphtha (petroleum), light arom.)
<b>Proper shipping name (ADN)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700) , Solvent naphtha (petroleum), light arom.)

### 14.3. Transport hazard class(es)

<b>ADR/RID class</b>	9
<b>ADR/RID classification code</b>	M6
<b>ADR/RID label</b>	9
<b>IMDG class</b>	9
<b>ICAO class/division</b>	9
<b>ADN class</b>	9

### **Transport labels**



### 14.4. Packing group

<b>ADR/RID packing group</b>	III
<b>IMDG packing group</b>	III
<b>ADN packing group</b>	III
<b>ICAO packing group</b>	III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

<b>EmS</b>	F-A, S-F
<b>ADR transport category</b>	3
<b>Emergency Action Code</b>	•3Z
<b>Hazard Identification Number (ADR/RID)</b>	90
<b>Tunnel restriction code</b>	(E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

## Epoxy Resin ER2225, Part A

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

<b>National regulations</b>	Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

#### **15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

#### **Inventories**

##### **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

### SECTION 16: Other information

<b>Abbreviations and acronyms used in the safety data sheet</b>	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IATA: International Air Transport Association. ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate. LC <sub>50</sub> : Lethal Concentration to 50 % of a test population. LD <sub>50</sub> : Lethal Dose to 50% of a test population (Median Lethal Dose). EC <sub>50</sub> : 50% of maximal Effective Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.
---	---

<b>Classification abbreviations and acronyms</b>	Eye Irrit. = Eye irritation Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation Aquatic Chronic = Hazardous to the aquatic environment (chronic)
--	---

<b>Classification procedures according to Regulation (EC) 1272/2008</b>	Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: Skin Sens. 1 - H317: : Calculation method. Aquatic Chronic 2 - H411: : Calculation method.
---	---

<b>Training advice</b>	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
------------------------	--

<b>Issued by</b>	Bethan Massey
------------------	---------------

<b>Revision date</b>	02/03/2017
----------------------	------------

## Epoxy Resin ER2225, Part A

<b>Revision</b>	0
<b>SDS number</b>	1163
<b>Hazard statements in full</b>	H226 Flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.