

APLBL APL Bead Lacquer

APL is a flexible, fast drying transparent acrylic conformal coating, used for the protection of electronic circuitry. APLBL is a high viscosity version of APL for improved coverage over sharp corners and component legs.

- High viscosity for improved edge coverage
- Formulated for dispensing applications
- Good clarity and high level of stability when exposed to UV light
- Offers good protection in humid environments and resistant to mould growth

Approvals	RoHS Compliant (2015/863/EU):	Yes
Liquid Properties	Appearance	Pale Coloured Liquid
	Density @ 20°C (g/ml)	0.97-0.99
	Flash Point	22°C
	VOC Content	54 ± 1.0%
	Solids Content	46 ± 1.0%
Dry Film Coating	Colour	Colourless
	Operating Temperature Range	-55°C to +125°C
	Flammability	Self-extinguishing (ASTM Method D635) Meets UL94-V1
	Dielectric Strength	45kV/mm
	Dielectric Constant	2.5
	Surface Insulation Resistance	1 x 10 ¹⁵ Ω
	Comparative Tracking Index	>300 Volts
	Dissipation Factor @ 1MHz @ 25°C	0.01
	Moisture Resistance (MIL-1-46058C)	Meets approval

<u>Description</u>	<u>Packaging</u>	<u>Order Code</u>	<u>Shelf Life</u>
APL Bead Lacquer	32oz cartridge	EAPLBL32OZ	12 months

Revision 4: February 2019

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way,
 Ashby de la Zouch,
 Leicestershire LE65 1JR
 T +44 (0)1530 419 600
 F +44 (0)1530 416 640
 BS EN ISO 9001:2008
 Certificate No. FM 32082