

FASTEN ALUMINUM SUN SHADE TO
BRICK OR STONE VENEER
W/ HILTI HIT-SC 16x85 MESH SLEEVE
W/ HIT HY70 ADHESIVE
W/ 3/8" x 6" F1554 STAINLESS STEEL
OR GALVANIZED THREADED ROD
- (2) @ 12" o.c. (10 TOTAL)

4" STANDARD BRICK
(STONE @ (3) LOCATIONS)

7/16" OSB SHEATHING
W/ #15 FELT AIR
INFILTRATION BARRIER

AIR SPACE

2x6 WOOD STUDS @
16" O.C. W/ 6" UNFACED
BATT INSULATION & 6
MIL. VAPOR RETARDER

HOHMANN & BARNARD
DW-10HS W/VEE TIES
FASTEN TO WOOD STUDS
& HEADER @ 16" o.c. W/
1/4" x 3" LAG SCREWS

H1, H4 OR H7 HEADER W/
6"x4" MASONRY SUPPORT
ANGLE OVER WINDOW
OPENING - SEE
STRUCTURAL

5/8" GYPSUM WALL
BOARD RETURN W/
J-TRIM

SHIM SPACE

2'-0"

(2) 2" WIDE x 6" TALL
STACKED EXTRUDED
ALUMINUM FRAME TO
MATCH WINDOW,
PROVIDED BY WINDOW
SUPPLIER, CAULK AND
SEAL AS REQUIRED


40 MIL ADHESIVE
FLASHING W/ MORTAR
NET, CELL VENTS @
32" oc

FLASHING, BACKER
BEAD & CAULK BY
WINDOW INSTALLER

1" INSULATED GLASS
SET IN ALUMINUM
FRAMES

(2) 2" WIDE x 6" TALL
STACKED EXTRUDED
ALUMINUM FRAME TO
MATCH WINDOW,
PROVIDED BY WINDOW
SUPPLIER, CAULK AND
SEAL AS REQUIRED

1'-0"



HEAD DETAIL

SCALE: 1 1/2" = 1'-0"