



PRODUCT SPECIFICATION

GENERAL

FINISH:	Anodised Aluminium	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.33 (kg)
DIMENSIONS:	D: 95mm DIA: 42mm	CLASS:	CE (Class III)
INSTALLATION ORIENTATION:	Ground/Floor	IP RATING:	IP67
CUT OUT HOLE:	40mm/1-9/16"	BATHROOM ZONE:	Zone 1, 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Constant Current 700 (mA)
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials


LAMP

LIGHT SOURCE:	High Power LED	MACADAM ELIPSE:	To Be Advised
MAXIMUM WATTAGE:	3W	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	24.9 (Degrees)
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	102.2 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	3000 (K)	AVERAGE LIFESPAN:	60,500 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	To Be Advised		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	Not Applicable
DIMMABLE:	Yes	DRIVER/BALLAST VOLTAGE:	Not Applicable
DIMMING METHOD:	Control Gear Dependant	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	Control Gear Dependent
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	No

ADDITIONAL INFORMATION



BOX QUANTITY X50

PRODUCT ELEVATIONS



40mm/1-9/16"

