




ENERG
енергия · ενεργεια





METROAIR I 20



55 °C


35 °C



dB



55 dB



2019


811/2013




ENERG Y IJA
 енергия · ενεργεια IE IA





METROAIR I 16 + METROAIR 330



A+++



A





ENERG

енергия · ενέργεια

Y






IJA


IE


IA





METROAIR I 20 + METROAIR 330













+ 

+ 

+ 


+ 

Supplier's name:	METRO THERM A/S		
Model:	Metroair I 20 + Metroair 330		
Temperature application	35	55	°C
Declared load profile for water heating	XL		
Seasonal space heating energy efficiency class, average climate:	A+++	A+++	
Water heating energy efficiency class, average climate:	A		
Rated heat output, average climate:	11	12,3	kW
Annual energy consumption for space heating, average climate	4502	6524	kWh
Annual electricity consumption for water heating, average climate	1616		kWh
Seasonal space heating energy efficiency, average climate:	199	153	%
Water heating energy efficiency, average climate:	104		%
Sound power level LWA indoors	35		dB
Rated heat output, cold climate:	13,0	14,0	kW
Rated heat output, warm climate:	13,0	13,0	kW
Annual energy consumption for space heating, cold climate	7543	9765	kWh
Annual electricity consumption for water heating, cold climate	1758		kWh
Annual energy consumption for space heating, warm climate	3153	3867	kWh
Annual electricity consumption for water heating, warm climate	1448		kWh
Seasonal space heating energy efficiency, cold climate:	167	138	%
Water heating energy efficiency, cold climate:	95		%
Seasonal space heating energy efficiency, warm climate:	217	177	%
Water heating energy efficiency, warm climate:	116		%
Sound power level LWA outdoors	55		dB

Data for package fiche

Controller class	VI		
Controller contribution to efficiency	4,0		%
Seasonal space heating energy efficiency of package, average climate:	203	157	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A+++	%
Seasonal space heating energy efficiency of package, cold climate:	171	142	%
Seasonal space heating energy efficiency of package, warm climate:	221	181	%

Model(s):				Metroair I 20 + Metroair 330							
Type of heat source/sink:				Air-to-water							
Low-temperature heat pump:				No							
Equipped with supplementary heater:				Yes							
Heat pump combination heater:				Yes							
Climate condition:				Average							
Temperature application:				Medium temperature (55 °C)							
Applied standards: EN14825 and EN16147											
Rated heat output				Prated	12,3	kW	Seasonal space heating energy efficiency				
							η_s	153	%		
<i>Declared capacity for part load at outdoor temperature Tj</i>						<i>Declared coefficient of performance for part load at outdoor temperature Tj</i>					
Tj = -7 °C	Pdh	10,9	kW	Tj = -7 °C	COPd	2,48	-				
Tj = +2 °C	Pdh	6,7	kW	Tj = +2 °C	COPd	3,96	-				
Tj = +7 °C	Pdh	5,9	kW	Tj = +7 °C	COPd	4,67	-				
Tj = +12 °C	Pdh	6,0	kW	Tj = +12 °C	COPd	5,67	-				
Tj = biv	Pdh	10,9	kW	Tj = biv	COPd	2,48	-				
Tj = TOL	Pdh	11,6	kW	Tj = TOL	COPd	2,40	-				
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd		-				
Bivalent temperature				T _{biv}	-7	°C	Operation limit temperature				
Cycling interval capacity for heating				P _{cyc}		kW	Cycling interval efficiency				
Degradation co-efficient				Cdh	0,99	-	Heating water operating limit				
							WTOL	65	°C		
<i>Power consumption in modes other than active mode</i>						<i>Supplementary heater</i>					
Off mode	P _{OFF}	0,025	kW	Rated heat output		P _{sup}	0,7	kW			
Thermostat-off mode	P _{TO}	0,007	kW								
Standby mode	P _{SB}	0,025	kW	Type of energy input		Electric					
Crankcase heater mode	P _{CK}	0,037	kW								
<i>Other items</i>											
Capacity control	variable					Rated air flow rate, outdoors			4150	m ³ /h	
Sound power level, indoors/outdoors	L _{WA}	35/55	dB	Rated water flow rate, indoor heat exchanger			variable	m ³ /h			
Annual energy consumption	Q _{HE}	6524	kWh	Rated brine or water flow rate, outdoor heat exchanger				m ³ /h			
<i>For heat pump combination heater:</i>											
Declared load profile				XL				Water heating energy efficiency			
								η_{wh}	104	%	
Daily electricity consumption	Q _{elec}	7,36	kWh	Daily fuel consumption		Q _{fuel}		kWh			
Annual electricity consumption	AEC	1616	kWh	Annual fuel consumption		AFC		GJ			
Approved by:											
Contact details				METRO THERM A/S Rundinsvej 55 DK-3220 Helsingør www.metrotherm.dk							