## **SIEMENS**

## Data sheet

5TC1296

DELTA REFLEX SMOKE DETECTOR 230V CAN BE NETWORKED DIMENSIONS 115MM X 43MM TITANIUM WHITE



Model			
Type of certification / NCP	No		
Cable entry type	Base		
Design of fire alarm / Smoke detector	Yes		
Design of the product / explosion-proof design	No		
Design of transmission medium / wireless transmission	No		
General technical data			
Response value temperature	50 °C		
Outer diameter / of the enclosure	111 mm		
Loudness level	85 dB		
Voltage			
voltage supply	230 V AC and 9 V alkaline back-up battery (included in the scope of supply)		
Supply voltage			
Type of voltage / of the supply voltage	AC		
Protection class			
Protection class IP	IP30		

Appearance					
Color		white			
Product details					
Product component / Integrated / orientation lighting		No			
Product extension / optional / can be networked with		No	No		
wireless connection					
Product function					
Product function					
<ul> <li>of backup battery / rechargeable</li> </ul>		No	No		
Number					
Number of fire detectors / networkable		1			
Mechanical Design		_			
Height		40 mm			
Length		180 mm			
Mounting type		assembly			
Mounting type / mounting in cable duct		No			
Certificates					
Certificate of suitability					
<ul> <li>VdS approval</li> </ul>		Yes			
General Product	Declaration of		other		
Approval	Conformity				
sonstig			sonstig		
	EG-Konf.				

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TC1296

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/5TC1296/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=5TC1296

CAx-Online-Generator http://www.siemens.com/cax

Tender specifications http://www.siemens.com/specifications

