



# MASTER LEDtube InstantFit HF T5

## MAS LEDtube HF 1500mm HO 26W 865 T5

Philips MASTER LEDtube InstantFit T5 integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. The Philips MASTER LEDtube InstantFit T5 is the ideal solution for customers who have higher light output requirements and want to maximize value over lifetime. Full energy savings & longer lifetime result in attractive payback times and TCO benefits.

### Product data

General Information		Power (Rated) (Nom)	
Cap-Base	G5 [ G5]		26 W
Nominal Lifetime (Nom)	50000 h	Lamp Current (Max)	415 mA
Switching Cycle	50000X	Lamp Current (Min)	240 mA
B50L70	50000 h	Starting Time (Nom)	0.5 s
		Warm Up Time to 60% Light (Nom)	0.5 s
		Power Factor (Nom)	0.9
		Voltage (Nom)	100-135 V
Light Technical		Temperature	
Color Code	865 [ CCT of 6500K]	T-Ambient (Max)	45 °C
Luminous Flux (Nom)	3900 lm	T-Ambient (Min)	-20 °C
Luminous Flux (Rated) (Nom)	3900 lm	T-Storage (Max)	65 °C
Correlated Color Temperature (Nom)	6500 K	T-Storage (Min)	-40 °C
Color Consistency	<6	T-Case Maximum (Nom)	45 °C
Color Rendering Index (Nom)	83		
LLMF At End Of Nominal Lifetime (Nom)	70 %		
Operating and Electrical			
Input Frequency	39000-60000 Hz		

# MASTER LEDtube InstantFit HF T5

## Controls and Dimming

Dimmable No

## Mechanical and Housing

Product Length 1500 mm

## Approval and Application

Energy Saving Product Yes

Energy Efficiency Label (EEL) A++

Approval Marks TUV CE marking RoHS compliance KEMA Keur certificate

Energy Consumption kWh/1000 h 31 kWh

## Product Data

Full product code 871869668556300

Order product name MAS LEDtube HF 1500mm HO 26W 865 T5

EAN/UPC - Product 8718696685563

Order code 929001296302


Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 10

Material Nr. (12NC) 929001296302

Net Weight (Piece) 0.197 kg



## Dimensional drawing



TLED 230V 26W-49W 3700lm 6500K G5 ND


Product	D1	D2	A1	A2	A3
MAS LEDtube HF 1500mm HO 26W 865 T5	15.2 mm	21 mm	1447.8 mm	1454.9 mm	1462 mm

## Photometric data



# MASTER LEDtube InstantFit HF T5

## Photometric data



## Lifetime

