



DEVIreg™ 130

The DEVIreg™ 130 is a simple electronic thermostat to be installed directly on the wall, using a floor sensor (wire) to measure and control the desired floor temperature.

The thermostat has a dial for adjusting the temperature setting with a scale from 1 to 5.

Furthermore, the thermostat has an LED indicating the current mode (heating, standby or fault).



Benefits:


- Double pole safety breaker
- Sensor failure monitoring
- LED indication
- Frost protection

Standard compliance:

- EN/IEC 60730-1 (general) and EN/IEC 60730-2-9 (thermostat)

Approvals:



| Type | Value |
|--------------------------------|--|
| Operation voltage | 220 V- 240V~ 50/60 Hz |
| Standby power consumption | Max. 5 W |
| Relay: | |
| Resistive load | Max 16A / 3680W @ 230V |
| Inductive load | Cos Φ = 0.3 max. 1A |
| Sensing unit | NTC 15 kOhm at 25° C |
| Hysteresis | ± 0.2° C |
| Ambient temperature | -10° C. to +30° C |
| Frost protection | 5° C - ❄️ |
| Temperature range | 5° C - 45° C |
| Cable specification max | 1 x 4 mm ² or 2 x 2,5 mm ² |
| Ball pressure test temperature | 75° C |
| Pollution degree | 2 (domestic use) |
| Controller type | 1 C |
| Storage temperature | -20° C to +65° C |
| IP class | 30 |
| Protection class | Class II -  |
| Dimensions (H/W/D) | 82 mm x 82 mm x 36 mm |
| Weight | 90 g |

Types

| Item no. | Product name | Type | EAN no. |
|----------|--------------|-------------------|---------------|
| 140F1010 | DEVIreg™ 130 | With floor sensor | 5703466208953 |