

**Floorstanding WC rimless combination with cistern
without fixing holes for floor fixation
82896.7**



TECHNICAL DATA

Order no.	82896.7
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 737 with cistern flushing mechanism, water condensation insulation, water inlet bottom right 1/2" brass
Special specification	with shut-off valve, Charge 738
Outlet	vertical
Weight	41,5 kg
Accessories excl.	Seat and cover, order no. 89095.0, 89115.0, 89115.2 Seat and cover with automatic lowering system, order no. 89095.1, 89115.1
Colours	see colour table

SPECIFICATION TEXT

Floorstanding WC rimless washdown LAUFEN PRO N, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)
EN 997, 4,5/3-l-flush, dimensions 365 x 650 x 890 mm
outlet vertical 70 mm
Special feature: concealed surfaces directing water are fully glazed throughout, open water rim, vacuum checked
Further options / accessories: Surface refinement LCC, with shut-off valve option 738, WC seat and cover 89095.0, 89115.0, 89115.2, WC seat and cover with automatic lowering 89095.1, 89115.1
Order no. 82896.7

TECHNICAL DRAWINGS / S 1 : 20

