Laserliner®

DampFinder Compact







- Quick localisation of moisture: comparison measurements can be made in Indicator-mode which reveal increasing or decreasing moisture
- Sturdy, ergonomically designed rubberised casing: The device can be comfortably held in one hand, meaning that the measuring spikes can be safely inserted.
- **Self-test function:** A reference measurement in the protective cap verifies the accuracy of the measuring device.
- measuring spikes against damage during transport.
- Ambient temperature sensor: The device shows the current ambient
- Simple one-button operation
- Auto power off



- Triple scale: for 2 wood groups and universal index mode
- based on a neutral scale.
- Large LC display with bar graph and numerical







Low battery display



ARTICLE	ARTICLE NO	EAN-CODE	PU
DampFinder Compact	082.015A	4 021563 690015	5

TECHNICAL DATA

MATERIALS

102 types of wood, aerated concrete, anhydrite screed, cement screed, chalky sandstone, concrete (C12/15, C20/25, C30/37), gypsum plaster

MEASUREMENT RANGE / ACCURACY

± 1% (5%...30%) ± 2% (30%...50%) WOOD INDEX ± 10 digits

NOMINAL TEMPERATURE 22°C

OPERATING TEMPERATURE 0°...40°C

STORAGE TEMPERATURE -10°C...70°C

MAX. RELATIVE HUMIDITY 85%

POWER SUPPLY

Batteries 4 x 1,5 V Typ AAA

BATTERY SERVICE LIFE approx. 700 hours

WEIGHT (incl. batteries) 183 g

DIMENSIONS (W x H x D) 58 mm x 155 mm x 38 mm



DampFinder Compact

- + batteries (4 x 1,5V AAA)
- + protective cap with self-test function

 $\textbf{Packing dimension} \; (\text{W} \; \text{X} \; \text{H} \; \text{X} \; \text{D})$ 190 x 310 x 56 mm

