

## Laserliner

## EasyCross-Laser **Green Set**



### Green cross-line laser for height transmission and alignment

# Rev19W19



- Green laser technology
- Extremely bright green laser cross at front in the DLD design achieves high-quality lines as well as a clean and clear and therefore easily visible line image.
- Ideal for aligning tiles, wallpaper, pictures, etc.
- Automatic Level: automatic alignment by virtue of a magnetic pendulum system.
- Additional slope mode to align angled surfaces.
- Out-Of-Level: is indicated by optical signals when the unit is outside its self-levelling range.
- Transport Lock: a pendelum lock protects unit during transport.
- Green laser technology with 0°C...50°C temperature range.
- Height-adjustable bracket with 1/4" and 5/8" tripod threads and magnets

#### **TECHNICAL DATA**

SELF-LEVELLING RANGE ± 3°  $\textbf{ACCURACY} \pm 0,5 \text{ mm / m}$ LEVELLING automatic **OPERATION RANGE** (depending on room illumination) 15 m LASER WAVELENGHT 515 nm LASER CLASS 2 / < 1 mW POWER SUPPLY 3 x 1,5V alkaline batteries (type AAA, LR6) OPERATING TIME 9 Std. (alkaline batteries) **OPERATING CONDITIONS** 0...50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level STORAGE CONDITIONS -10°C...70°C, max. humidity 80% rH DIMENSIONS (W x H x D) 75 x 88 x 58 mm WEIGHT (incl. batteries) 202 g

1HG 1VG



EasyCross-Laser Green set + tripod-/wall mount + batteries

Packing dimension (W x H x D) 135 x 320 x 200 mm







Multi-functional tripod-/wall mount

ARTICLE	ARTICLE NO	EAN-CODE	PU
EasyCross-Laser Green Set	081.081A	4 021563 707232	5



UMAREX GmbH & Co. KG · Donnerfeld 2 · 59757 Arnsberg · Germany · Tel. +49 2932 638-300 · Fax +49 2932 638-333 · info@laserliner.com · www.laserliner.com