

**POWERPLUS**  
HIGH QUALITY TOOLS



**POWX07595**

# TABLE SAW

## 2000W | 250mm

TAFELZAAG  
SCIE À TABLE  
TISCHKREISSÄGE  
SIERRA DE MESA



IMPORTANT FEATURES

EXTENDABLE TABLE

BLADE TILTING RANGE 0-45°

DUST EXTRACTION OUTLET

MAGNETIC ON/OFF SWITCH

+ SAW BLADE

+ PUSH STICK

**2000**  
WATT

**5000**  
min<sup>-1</sup>

**Ø250**  
mm

**3**  
YEAR  
WARRANTY

### 1 SAW BLADE GUARD

BESCHERMKAP ZAAGBLAD / PROTECTION DE LA LAME  
SÄGEBLATTABDECKUNG / PROTECCIÓN DE LA HOJA

### 2 EXTRACTION HOSE

AFZUIGSLANG / TUYAU D'ASPIRATION  
ABSAUGSCHLAUCH / MANGUERA DE EXTRACCIÓN

### 3 SAW BLADE HEIGHT SETTING & TILTING RANGE

HOOGTE-INSTELLING & AFSCHUINHOEK ZAAGBLAD  
RÉGLAGE DE LA HAUTEUR & PLAGE D'INCLINAISON DE LAME DE SCIE  
HÖHENEINSTELLUNG & ANSTELLWINKEL DES SÄGEBLATTES  
AJUSTE DE LA ALTURA & RANGO DE INCLINACIÓN DE HOJA DE SIERRA

### 4 MITRE ANGLE GUIDE

VERSTEKGELEIDER / BUTÉE D'ANGLE À ONGLET  
WINKELANSCHLAG / TOPE ANGULAR DE INGLETE

### 5 LOCK FOR SAW BLADE ANGLE ADJUSTMENT

VERGREDELING HOEKINSTELLING ZAAGBLAD  
VERROUILLAGE DU RÉGLAGE D'ANGLE DE LA LAME  
VERRIEGELUNG FÜR WINKLEINSTELLUNG  
BLOQUEO DEL AJUSTE DEL ÁNGULO DE LA HOJA

### 6 MAGNETIC ON/OFF SWITCH + EMERGENCY STOP

MAGNETISCHE AAN-/UITSCHAKELAAR + NOODSTOP  
INTERRUPTEUR MARCHE-ARRÊT MAGNÉTIQUE + ARRÊT D'URGENCE  
MAGNETISCHER EIN-/AUSSCHALTER + NOT-HALT  
INTERRUPTOR MAGNÉTICO DE ENCENDIDO/APAGADO + PARADA DE EMERGENCIA

### 7 TILT PROTECTION



KANTELBEVEILIGING / DISPOSITIF ANTI-BASCULEMENT  
KIPPSCHUTZ / PROTECCIÓN DE INCLINACIÓN

### 8 PARALLEL GUIDE

PARALLELGELEIDER / GUIDE PARALLÈLE / PARALLELFÜHRUNG / GUÍA PARALELO

### 9 MAXIMUM CUTTING CAPACITY

MAXIMALE SNIJ/ZAAGCAPACITEIT / CAPACITÉ DE COUPE MAXIMALE  
MAX. SCHNEIDLEISTUNG / CAPACIDAD MÁXIMA DE CORTE



**POWERPLUS**  
HIGH QUALITY TOOLS



POWX07595

# TABLE SAW 2000W

Lay your wooden boards comfortably on the large table of this Powerplus table saw and work on an ergonomic working height of 820mm. With 2000W power and a rotation speed of 5000min<sup>-1</sup> you make straight and cross cuts in wood. You get perfectly sawn wider boards, as you even have the possibility to extend the table on the left and the right as well as at the back.

You can easily adjust the angle and height of the Ø 250mm saw blade. The mitre gauge fence and parallel guide give you the opportunity to make very accurate parallel cuts in wood up to 85mm thick and mitre cuts up to 63mm deep. A push stick and a saw blade guard guarantee your safety while sawing and the overload protection avoids overheating. You can attach the dust extraction outlet to a vacuum cleaner to guarantee a clean, dust-free working environment.



TECHNICAL SPECIFICATIONS POWX07595		Features	Box content	Symbols
Rated voltage - frequency	220-240V~ 50Hz	<ul style="list-style-type: none"> <li>Saw blade height setting &amp; tilting range</li> <li>Saw blade guard</li> <li>Parallel guide</li> <li>Angle guide</li> <li>Overload protection</li> <li>Table extension</li> <li>Tilt protection</li> <li>Rubber feet</li> <li>Extraction hose</li> </ul>	1x table saw / 1x saw blade 24T	   
Rated power	2000W		1x blade guard / 3x table extension	
Rotation speed	5000min <sup>-1</sup>		1x extraction hose	
Max. cutting capacity	90°: 85mm / 45°: 63mm		1x mitre angle stop	
Table size	563x583mm		1x push stick / 1x parallel stop	
Extended table size	165x583mm		4x supporting leg	
Rear extension table size	560x220mm		8x bracket	
Work table height	820mm		2x blade wrenches	
Blade dimensions	Ø250x30mm - 24T		1x manual	

**KREATOR**

KREATOR ACCESSORIES COMPATIBLE WITH POWX07595

<b>SAW BLADE</b>	<b>SAW BLADE</b>	<b>ROLLER SUPPORT STAND</b>
KRT020425 WOOD - 48T	KRT020426 WOOD - 80T	POWX0700T

**VARO**

VARO - VIC. VAN ROMPUY nv - DIY & GARDEN TOOLS  
JOSEPH VAN INSTRAAT 9 - B-2500 LIER - BELGIUM  
TEL +32 (0)3 292.92.92 | FAX +32 (0)3 292.92.72  
INFO@VARO.COM | WWW.VARO.COM

Box (piece)



5 400338 090721 >

Our +50 years of experience guarantee a professional and high quality service.