

PRODUCT-DETAILS

TAC-W22-T-R-0

TAC-W22-T-R-0 Terra AC wallbox type 2, socket, three phase/32A, with RFID



General Information

Extended Product Type	TAC-W22-T-R-0
Product ID	6AGC082152
EAN	8719874450904
Catalog Description	TAC-W22-T-R-0 Terra AC wallbox type 2, socket, three phase/32A, with RFID
Long Description	TAC-W22-T-R-0 AC wallbox type 2, socket, three phase/32A, with RFID

Technical

Output Power	AC 22.1 kW
Number of EV Connectors	No cable outlet
Number of Socket Outlets	(AC Type 2) 1 piece
Output Voltage (U _{out})	380 ... 415 V AC
Output Current	3 phase 32 A
Connection Power	22.5 kW
Supply Voltage	AC 380..415 V
Input Current	3 phase 32 A
Operating Frequency (f _{sw})	50 ... 60 Hz
Number of Phases	3
Connection Configuration	TT, TN
Number of Miniature Circuit Breakers (MCBs)	0

Overvoltage Category	III
Overload Protection	Overcurrent protection at 40 A
Ambient Air Temperature	Operation -30... +50 °C Storage -50 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Communication Interface	Wi-Fi Bluetooth
Authentication Method	RFID
Enclosure Type	indoor, outdoor
Mounting Type	Wall mounting
Degree of Protection	acc. to IEC 60529 IP54
Impact Resistance Rating	IK08

Dimensions

Package Level 1 Units	carton 1 piece
Package Level 1 Width	0.26 m
Package Level 1 Height	0.2 m
Package Level 1 Depth / Length	0.40 m
Package Level 1 Gross Weight	3.5 kg
Package Level 1 EAN	8719874450904
Package Level 2 Units	crate 8 piece
Package Level 2 Width	0.90 m
Package Level 2 Height	0.20 m
Package Level 2 Depth / Length	1.00 m
Package Level 2 Gross Weight	28 kg

Ordering

Customs Tariff Number	85371098
Minimum Order Quantity	8 piece
EAN	8719874450904
ETIM 7	EC002883 - Charging device E-Mobility
UNSPSC	25175002

Additional Information

Housing Material	Plastic
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
Load Management Method	OCP - Based
Standards	EN 61851-1 EN 61851-23 EN 61000-6-2 EN 61000-6-3 EN 301 908-2 IEC 60721-3-2: IE23 RoHS
Declaration	CE

Categories

Electric Vehicle Infrastructure → AC Charging → AC Chargers CE

