

LC-Click 200

Product Information

- Motion detector with 200° detection area and 180° anti-creep zone
- Adjustable ball head
- Simple mounting thanks to plug base
- Can be mounted on standard flush-mount boxes
- Detection area can be restricted with blinds
- **Application examples:**
for narrow premises, garage entrances, door sills

Technical Data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	103 x 78 x 80 mm
Power consumption:	approx. 0.4 W
Detection area:	horizontal 200° (Wall mounting)
Range:	max. 12 m across max. 4 m towards max. 2 m anti-creep protection
Monitored area (tangential movement):	250 m ² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 3 m / 2.5 m
Degree / class of protection:	IP44 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
	Channel 1 (lighting control)
Switching power:	1000 W, cos φ = 1 500 VA, cos φ = 0.5 300 W LED
Type of contact:	1x μ-contact, NO contact

Follow-up time: 4 sec - 20 min

Switch-on threshold: 2 - 2000 Lux

Description

Description	Colour	Part number	EAN number
LC-Click 200	white mat, similar to RAL9010	91102	4007529911028

Accessory

Description	Colour	Part number	EAN number
Wire basket BSK (Ø 164 x 143 mm)	white	92467	4007529924677
RC-Arc extinction kit	white	10880	4007529108800
Mini-RC-Arc extinction kit	black	10882	4007529108824

© 2021 B.E.G. Brück Electronic GmbH