Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name	e or trade mark:	Halo Design				
Supplier's address: Energimærkning, Gammelgårdsvej 85, 3520 Farum, DK						
Model identifie	er: 931217					
Type of light so	urce:					
Lighting techno	logy used:	LED	Non-directional or directional:	DLS		
Light source cap-type		socket				
(or other electri	ic interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	Nej		
Colour-tuneable	e light source:	Nej	Envelope:	-		
High luminance	light source:	Nej				
Anti-glare shield	d:	Nej	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		1	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		40 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W		1,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	177	Spectral power	See image		
dimensions	Width	180	distribution in the	in last page		
without	Depth	180		 		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,100			
		coordinates (x and y)	0,100			
Parameters for directional light sources:						
Peak luminous intensity (cd)	1	Beam angle in	1			
		degrees, or the				
		range of beam				
		angles that can be				
		set				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	1	Survival factor	1,00			
the lumen maintenance factor	1,00					

(a)'-': not applicable; (b)'-': not applicable;

