Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	LLLOAILD KLOOI	-A11011 (LO) 2013/20	ora with regard to energ	gy labelling of light		
Supplier's name or trade mark: Halo Design						
Supplier's address: Energimærkning, Gammelgårdsvej 85, 3520 Farum, DK						
Model identifie	er: 936267					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		1				
(or other electric interface)						
Mains or non-m	nains:	MLS	Connected light source (CLS):	Nej		
Colour-tuneable	e light source:	Nej	Envelope:	-		
High luminance light source:		Nej				
Anti-glare shield	d:	Nej	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1 800		
On-mode power (P _{on}), expressed in W		5,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	165	Spectral power	See image		
dimensions	Width	135	distribution in the	in last page		
without	Depth	135		 Side 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,100			
		coordinates (x and y)	0,100			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	1	Survival factor	1,00			
the lumen maintenance factor	1,00					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	1,00	Colour consistency in McAdam ellipses	1			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

