## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: UMAGE	
--------------------------------------	--

Supplier's address: UMAGE ApS, Havnegade 29, 1058 Copenhagen, DK

Model identifier: 2165 (light-source)

_	•			
Type	Λt	liont	COLL	rca.
IVDE	VI.	HEIL	3UU	ıcc.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	LED Spot		
(or other electric interface)	1,3W 0,4A		
Mains or non-mains:	NMLS	Connected light source (CLS):	Nej
Colour-tuneable light source:	Nej	Envelope:	-
High luminance light source:	Nej		
Anti-glare shield:	Nej	Dimmable:	No
Product parameters			
Parameter	Value	Parameter	Value
General product parameters:			

Parameter		Value	Parameter	Value	
	General product parameters:				
0,	mption in on- 100 h), rounded st integer	2	Energy efficiency class	F	
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	125 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode prespressed in W	oower (P <sub>on</sub> ),	1,3	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00	
for CLS, expres	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82	
Outer	Height	23	Spectral power	See image	
dimensions	Width	23	distribution in the	in last page	
without	Depth	19		Sido 1 / 2	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity	0,444
		coordinates (x and y)	0,414
Parameters for LED and OLED light sources:			
R9 colour rendering index value	3	Survival factor	1,00
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

