



QuickFix® Extension 3

Predecessor: 014-014 001-106 QUICK-FIX3MWH

Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our patented QuickFixTM system: Using this to history with our patentied QuickFix* "system. Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix* product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix* cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

Dimensions



Length: 3.00 m Number of segments: 1 Length per segment: 3.00 m Max. Wattage: 1800 W

Operating voltage: 220-240 V AC 50-60Hz

Operating mode: Outlets: 1 Connectable: yes



Packaging - Product

Type of Packaging: Blister with headcard EAN-Code: 9120079030102 Size (L-W-H): 17 x 25 x 0 cm Weight: 0.29 kg Produkts/Packaging: 1

Packaging - Inner Box

Type of Packaging: White carton EAN-Code: 9120079039358 Size (L-W-H): 28 x 20 x 8 cm Weight: 1.64 kg Produkts/VPE: 5

Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120079034896 Size (L-W-H): 42 x 30 x 26 cm Weight: 10.44 kg Produkts/VPE: 30