



Capsules LV 3000 h



Caps 3000h 35W GY6.35 12V CL 1CT/10x10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact halogen capsule delivers crisp white light over a long lifetime.

Product data


General Information	
Cap-Base	GY6.35 [GY6.35]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)	3000 h
Switching Cycle	12000X
Rated Lifetime (Hours)	3000 h
Flux measurement reference	Sphere
Light Technical	
Luminous Flux (Nom)	766 lm
Luminous Flux (Rated) (Nom)	766 lm
Chromaticity Coordinate X (Nom)	0.43
Chromaticity Coordinate Y (Nom)	0.402
Correlated Color Temperature (Nom)	3100 K
Luminous Efficacy (rated) (Nom)	21.9 lm/W
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Nom)	36 W
Lamp Current (Nom)	2.917 A
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	instant full light s
Power Factor (Nom)	1

Voltage (Nom)	12 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T11 [T 11mm]
Approval and Application	
Energy Efficiency Class	G
Energy Consumption kWh/1000 h	36 kWh
EPREL Registration Number	423256
Luminaire Design Requirements	
Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	350 °C
Product Data	
Full product code	871869682783300
Order product name	Caps 3000h 35W GY6.35 12V CL 1CT/10x10F
EAN/UPC - Product	8718696827833
Order code	925723717101
Numerator - Quantity Per Pack	1

Capsules LV 3000 h

Numerator - Packs per outer box	100
Material Nr. (12NC)	925723717101
Net Weight (Piece)	0.003 kg

Dimensional drawing



EcoHalo Capsule Gy6.35 12v35w CL B3000

Product	D (max)	L	C (max)
Caps 3000h 35W GY6.35 12V CL 1CT/10x10F	12 mm	30 mm	44 mm

