

Product No. **7352-400-12**
 S No. **4212088**
 EAN No. **7312907352124**



Cool high

A smart and slick external downlight of ceramic in a timeless elegant design. Suitable both indoors and outdoors.

Specification

| | |
|------------------|-------------------------|
| Base material | Porcelain |
| Lampholder | GX53 |
| Light source | Max 9W (not incl.) |
| Voltage | 230V |
| Installation | Ceiling/wall |
| Base colour | Grey NCS S 6005-G50Y |
| Safety class | II |
| Protection class | IP44 |
| Energy class | - |
| T _a | -30 - +25 |
| Height | 66 mm |
| Diameter Ø | 120 mm |
| Glass | Protection glass, clear |
| Thread | 99 mm |
| Weight | 1 kg |
| Design | Håkan Svennesson SD |

Installation

Insert the mains supply cable through the bottom inlet. Remove the lamp holder. Fix the light fitting to the wall or to the ceiling with suitable screws. Connect the leads to the terminals. Fasten the lamp holder. Insert a light source and then tighten the upper part of the light fitting by turning it clockwise. Make sure the gasket between the two ceramic parts is in place.

Technical information

Silicone gasket between glass and base. Two Ø 5 mm holes for installation, CC measurement 70 mm. One bottom inlet for two mains supply cable. Terminal for connection of max 3 x 2.5 mm². Bridging is possible. Bottom inlet and two knock out openings. Maximum measurement for lightsource: Ø75 mm, height 24mm.

Maintenance

Switch off the power to the fixture. Remove the top and clean it. Do not use cleaning agents containing solvents. Change the light source if necessary. Check the gasket and change if necessary. Replace the top onto the socket.

Spare parts

Cover: Part no Cool IP44 52801-12
 Gasket: Part no 03542

If the luminaire is modified the person responsible for the modification shall be considered manufacturer. Subject to errors in text. We reserve the right to change the technical specifications (without notice).

