


M371S

Flush plate with sensor for pre-wall installation systems, chrome-polished (AC power supply)



Application

Can not be used for pre-wall installation systems Slim
 For touchless flushing with a sensor
 For pre-wall installation systems and concealed WC cisterns

Features

- Magnetic switch for service setting and cleaning
- Material: plastic
- Option to use the button for a large flush
- Powered by the main electric supply, the power source must be purchased (12 V DC min 1 A) – recommended AEZ310
- Setting via mini USB using free software available on the Alcaplast website
- Adjustable parameters: start and end time of registration, duration of flushing, automatic flush, allowing flooding, flooding time, variable settings hygienic rinse
- Surface finish: chrome-polished

Scope of supply

- Infrared sensor
- Connector for attaching to the source
- Screw set with a solenoid valve
- Flush plate
- Fixing frame of the flush plate
- Flush valve for sensor flushing
- Threaded frame clamp 2 pcs

Order number, Logistic information

Code	EAN	Weight (kus packing palett)	Dimensions (piece packing)	Quantity (packing palett)
M371S	8595580501716	1,5255 15,2550 264,0800 kg	315×210×120 595×395×435 mm	10 160 pcs

Guarantee 2/2 years **Customs code** 84818019 **Norms** EN 55014, EN 55022, EN 61000

Technical specifications

- Operating force < 20 N
- Power consumption 8,5 W
- Output voltage 12 V DC