

# Product data sheet

Specifications



## TeSys GC - modular contactor - 25 A - 4 NO - coil 220...240 V AC

GC2540M5

### Main

Range	TeSys
Product name	TeSys GC
Product or component type	Modular contactor
Device short name	GC25
Contactor application	Lighting Motor control Heating

### Complementary

Utilisation category	AC-7B AC-7A
Poles description	4P
Power pole contact composition	4 NO
[Ue] rated operational voltage	$\leq 250$ V AC
[Ie] rated operational current	25 A AC-7A 8.5 A AC-7B
Operating position	30°/vertical
Control circuit type	AC at 50 Hz
[Uc] control circuit voltage	220...240 V AC 50 Hz
[Uimp] rated impulse withstand voltage	4 kV
[Ith] conventional free air thermal current	25 A (at 50 °C) for power circuit
Irms rated making capacity	68 A at 400 V AC for power circuit conforming to IEC 61095
Rated breaking capacity	68 A at 400 V for power circuit conforming to IEC 61095
[Icw] rated short-time withstand current	200 A 40 °C - 10 s for power circuit 62 A 40 °C - 30 s for power circuit
Associated fuse rating	25 A gL at $\leq 440$ V for power circuit
Average impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
[Ui] rated insulation voltage	500 V conforming to IEC 61095 500 V conforming to VDE 0110
Electrical durability	AC-7A: 100000 cycles AC-7B: 100000 cycles
Power dissipation per pole	1.6 W

<b>Control type</b>	Remote control
<b>Mounting mode</b>	Clip-on
<b>Mounting support</b>	DIN rail
<b>Standards</b>	IEC 61095 IEC 60947-5
<b>Connections - terminals</b>	Control circuit: screw clamp terminals 1 cable(s) 2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1.5 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 1 cable(s) 6 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 4 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 6 mm <sup>2</sup> flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 1.5 mm <sup>2</sup> flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 6 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 2 cable(s) 4 mm <sup>2</sup> solid without cable end
<b>Tightening torque</b>	Control circuit: 0.8 N.m - on screw clamp terminals Power circuit: 0.8 N.m - on screw clamp terminals
<b>Operating time</b>	10...25 ms opening 10...30 ms closing
<b>Mechanical durability</b>	1000000 cycles
<b>Maximum operating rate</b>	300 cyc/h 50 °C
<b>Control circuit voltage limits</b>	Drop-out: 0.2...0.75 U <sub>c</sub> at 50 Hz (at <50 °C) Operational: 0.85...1.1 U <sub>c</sub> at 50 Hz (at <50 °C)
<b>Inrush power in VA</b>	34 VA 50 Hz (at 20 °C)
<b>Hold-in power consumption in VA</b>	4.6 VA 50 Hz (at 20 °C)
<b>Heat dissipation</b>	1.6 W at 50/60 Hz

## Environment

<b>IP degree of protection</b>	IP40 conforming to VDE 0106 (in enclosure) IP20 conforming to VDE 0106
<b>Protective treatment</b>	TC
<b>Ambient air temperature for operation</b>	-5...50 °C
<b>Ambient air temperature for storage</b>	-40...70 °C
<b>Operating altitude</b>	<= 3000 m
<b>Mechanical robustness</b>	Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 3 Gn, 5...300 Hz
<b>Total number of 18 mm modules</b>	2
<b>Height</b>	85 mm
<b>Width</b>	36 mm
<b>Depth</b>	62.5 mm
<b>Net weight</b>	0.23 kg
<b>Quantity per set</b>	Set of 6
<b>Colour</b>	White

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	203.0 g

Package 1 Height	9 cm
Package 1 width	23 cm
Package 1 Length	8 cm
Unit Type of Package 2	P06
Number of Units in Package 2	576
Package 2 Weight	136.7 kg
Package 2 Height	77 cm
Package 2 width	80 cm
Package 2 Length	60 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	6
Package 3 Weight	1.28 kg
Package 3 Height	9 cm
Package 3 width	23 cm
Package 3 Length	8 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Contractual warranty

Warranty	18 months
----------	-----------