



RUSTY SLOT 50

outdoor floor stand, LED, 3000K, rusted steel, L/W/H
12/12/50 cm

The direct radiating floor stands of the RUSTY series convince by their exceptional rust look. This is achieved by a special chemical treatment of the FeCSi steel used. This makes the luminaire a unique piece and an absolutely special feature wherever they are installed. With protection class IP55, it is suitable for outdoor use. As an option an earth spike as well as a connection box for safe electrical connection to the round luminaire upright, are available. Equipped with a high output COB LED, the luminaire connects directly to 230V mains supply.

TECHNICAL DATA

Item no.	233447
IP Code	IP 55
Assembly	Surface
Assembly details	Ground
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Stroboscopic effect (SVM)	3.25
Lumen	30 lm
Colour temperature	3000 Kelvin
Color	rust
CRI	80
LXXBXX data	L70B50
Service life	35000 h
Light distribution	symmetric
Light outlet	direct
Width	12 cm
Height	50 cm
Depth	12 cm
Net weight	12.456 kg

Light Source

954801	
--------	---

Accessories

228730	CONNECTION BOX , 3-pin, IP68
231230	EARTH SPIKE , for GRA- FIT, RUSTY SLOT, LOGS floor stand, galva- nised steel, length 48cm

Gross weight	12.901 kg
BIG WHITE Page	524