


WORKLIGHT

black free-standing lamp. 79W 4000K 80°

As a consistent further development of our WORKLIGHT series, this WORKLIGHT is an office free-standing light for VDU workstations, equipped with state-of-the-art technology and highly efficient, high-output LEDs and, of course, $UGR \leq 19$. Equipped with a motion sensor, the built-in daylight control and the possibility of dimming, it meets all the requirements of today's office lighting. The WORKLIGHT is ready for direct connection to a 230V mains power supply thanks to its pre-installed driver and supply cable including plug. This light contains integrated LED light bulbs.



TECHNICAL DATA

Item no.	1005390
Number of different light outlets	2
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Mobile
Dimmable	Yes
Dimming technology	Touch
Primary nominal voltage	200-240V ~50/60Hz
Secondary power / voltage	2000 mA
Safety class	I
Wattage	79 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	30 A
Duration of inrush current	150 µs
Stroboscopic effect (SVM)	0
Lumen	7600 lm
Colour temperature	4000 Kelvin
Beam angle	80 °
Color	black
CRI	80

Light Source

916336	
--------	---

UGR \leq	19
LXXBXX data	L80B10
Service life	50000 h
Risk Group	0
Length	69.2 cm
Width	31 cm
Height	195 cm
Net weight	14.535 kg
Gross weight	17.584 kg
BIG WHITE Page	101