

Technical specifications:

- Power supply: Power adapter 230 Vac - 50 Hz / 9 Vdc (supplied)
- Network interface: 1 RJ45 port, 10/100 base TX (network interface with auto-MDIX capability that lets you use either a crossover or a non-crossover network cable)
- Working power: 1.4W max.
- Protection class: IP40
- 360° directional radio antenna (with an option to use an extension cable for the antenna to remote the signal)
- Dimensions: 60 x 86 x 27 mm / 2.36 x 3.39 x 1.06 inch. (without antenna)
- Weight: 70 g (without power adapter)

Use exclusively the power unit supplied with the product with the following features:

Trademark: Power Max; Model: SW4311

100-240V AC 50/60Hz; Output: 9.0VDC 660mA

Complying with limited power source (LPS) requirements - Max. allowable temperature: +40°C

Details on the information provided by YOKIS HUB:



Operation:

1. Fixing the antenna
2. RADIO LED: indicates the exchange of data between the installed modules and YOKIS HUB
3. LED that indicates the YOKIS HUB status
4. Hidden button

Reading the HUB (3.) status :

- Standard operation: 1 flash every 3 seconds
- Error detected: flashing at a very slow rate (the LED lights up for 5 seconds, then goes off for 5 seconds)

Reading error messages (when the LED 3. blinks very slowly to indicate an error, the following sequences appear on LED 2):

- The Yokis Hub is not associated with a **Yno** account: short - long - long - long
- Empty database: short - short - short - short
- Cannot access the Yokis radio network: short - short - short - long
- Cannot access the Yokis Cloud: short - short - long - short
- IP Network error: short - short - long - long
- Network connection error: short - long - short - short
- Network cable not connected: short - long - short - long
- Material error: short - long - long - short

RADIO RANGE

POWER Range :

- Inside 100 m² apartments with perpendicular crossing of main wall or ceiling
- 250 m in open range

(Note: in both cases the range may be reduced by the presence of metallic elements, crossing of walls or partitions)

C €0536

CONTROL APPLICATION: YOKIS **Yno**

Check the system easily from home or on the go thanks to the mobile application YOKIS **Yno** (available for Android and iOS mobile phones and tablets).

Download the mobile phone and/or tablet application by scanning the QR code shown opposite or by visiting the website: <http://www.yokis.com/en/app-yno.html>



**All YOKIS radio receivers are compatible with YOKISHUB.
All YOKIS radio transmitters are compatible with YOKISHUB:
remote controls, wall-mounted remote controls and flush-mounted transmitters.**

Urmet S.p.a. – 10154 TORINO (ITALY) – Via Bologna 188/C

For technical information, go to www.yokis.com or call:

Customer Service: +39 011.23.39.810

Export dept. Phone: +39 011.24.00.250/256 – Fax: +39 011.24.00.296



WARRANTY: In addition to the warranty required by law, this product is **guaranteed for 5 years** from the date of manufacture. The material must be used according to the instructions provided and for its intended use. Faults must not be caused by deterioration or accidents resulting from negligence, anomalous use, or incorrect installation. In all cases, the warranty only includes replacement of faulty products. No compensation for loss or damages may be claimed.