

tesa® Powerbond INDOOR



BNR 55740, 55741, 55742, 55755, 55762, 55763, 65204

Product Features

- Ideal for interior use, extra-strong hold
- Holds up to 5 kg* per 10 cm tape
- Holds on tiles, plaster, wood and most plastics

*For flat objects up to 10 mm thick and on most smooth, sufficiently firm surfaces

Product Description

tesa® Powerbond INDOOR is a quick and easy way to wall-mount items on indoor surfaces at home. A perfect alternative to the mess of drilling.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-------------------------------|---------|--------------------|------------------|
| • Holding power of tape up to | 50 KG/M | • Backing material | PE foam |
| • Total thickness | 1100 µm | • Type of adhesive | synthetic rubber |

Properties/Performance Values

- | | | | |
|-------------------------------|---|-------------------------------|--|
| • Applicationfield | Bedroom, Children's room, Hall, Home, Living room, Office | • Temperature resistance min. | 5 °C |
| • Chemical resistance | no | • Suitable surfaces | Lacquered wood, Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel |
| • Residue free removal | no | • Ageing resistance (UV) | yes |
| • Application temperature | -10 °C | • Humidity resistance | no |
| • Temperature resistance max. | 40 °C | | |

tesa[®] Powerbond INDOOR

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=55740>