

CorePro LEDcapsule MV



CorePro LEDcapsule 3.2-40W ND G9 827

The LED specialties deliver a high quality light to make themselves to be a true replacement of halogen specialty lamp (such as G9 and R7S). It is particularly suit for task lighting in hotel and restaurants, and ideal for decorative and ambient application. LEDspecialty products deliver huge energy saving and minimize maintenance costs, without any compromise on light quality.

Product data

| General information | | |
|---------------------------------------|---------------------|--|
| Cap-Base | G9 [G9] | |
| CE mark | Yes | |
| EU RoHS compliant | Yes | |
| Nominal Lifetime (Nom) | 15000 h | |
| Switching Cycle | 8000 | |
| Flux measurement reference | Sphere | |
| Tier | CorePro | |
| | | |
| Light technical | | |
| Color Code | 827 [CCT of 2700K] | |
| Luminous Flux (Nom) | 400 lm | |
| Color Designation | Warm White (WW) | |
| Correlated Color Temperature (Nom) | 2700 K | |
| Luminous Efficacy (rated) (Nom) | 125.00 lm/W | |
| Color Consistency | <6 | |
| Color Rendering Index (Nom) | 80 | |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % | |
| | | |

| Operating and electrical | |
|---------------------------------|-------------|
| Input Frequency | 50 to 60 Hz |
| Power (Nom) | 3.2 W |
| Lamp Current (Nom) | 30 mA |
| Wattage Equivalent | 40 W |
| Starting Time (Nom) | 0.5 s |
| Warm Up Time to 60% Light (Nom) | 0.5 s |
| Power Factor (Nom) | 0.4 |
| Voltage (Nom) | 220-240 V |
| | |
| Temperature | |
| T-Case Maximum (Nom) | 82 °C |
| | |
| Controls and dimming | |
| Dimmable | No |
| | |
| Mechanical and housing | |
| Bulb Finish | Clear |
| Bulb Shape | Capsule |
| | |


Datasheet, 2022, December 5 data subject to change

CorePro LEDcapsule MV

| Approval and application | | |
|-------------------------------|--------------------------------------|--|
| Energy Efficiency Class | E | |
| Suitable For Accent Lighting | No | |
| Energy Consumption kWh/1000 h | 4 kWh | |
| EPREL Registration Number | 453190 | |
| | | |
| Product data | | |
| Full product code | 871951430393500 | |
| Order product name | CorePro LEDcapsule 3.2-40W ND G9 827 | |

| EAN/UPC - Product | 8719514303935 | |
|---------------------------------|---------------|--|
| Order code | 929002495502 | |
| Numerator - Quantity Per Pack | 1 | |
| Numerator - Packs per outer box | 12 | |
| Material Nr. (12NC) | 929002495502 | |
| Net Weight (Piece) | 0.012 kg | |
| | | |


Dimensional drawing



CorePro LEDcapsule 3.2-40W ND G9 827


| Product | D | С |
|--------------------------------------|---------|-------|
| CorePro LEDcapsule 3.2-40W ND G9 827 | 16.5 mm | 54 mm |

Photometric data



Cifo.LuX Photometrics 4.5 Philips Lighting 6.V. Page: UT


LEDCapsule Core-Pro 3,2W G9 827-GUL



LEDCapsule CorePro 3,2W G9 827-LDD


CorePro LEDcapsule MV


Photometric data



LEDCapsule CorePro 3,2W G9 827-POC

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.