



LED Worklamps	Reference	Description	Power (W)	Voltage (V)	Flux (lm)	Color temperature (K)	Degree of protection	USB	Socket
	IMT47270	Thorsman WL 2100 lm, 18 W, 2-Pin plug, w/o Earth	18	220-240	2100	4000	IP65	NA	NA
	IMT47271	Thorsman WL 4000 lm, 35 W, Schuko Soc, USB	35	220-240	4000	4000	IP54	Type A + C 2.4 A Max	Schuko
	IMT47272	Thorsman WL 6800 lm, 55 W, Schuko Soc, USB	55	220-240	6800	4000	IP54	Type A + C 2.4 A Max	Schuko
	IMT47273	Thorsman WL 8500 lm, 75 W, Schuko Soc, USB	75	220-240	8500	4000	IP54	Type A + C 2.4 A Max	Schuko
	IMT47274	Thorsman WL 4000 lm, 35 W, FR Socket, USB	35	220-240	4000	4000	IP54	Type A + C 2.4 A Max	French
	IMT47275	Thorsman WL 6800 lm, 55 W, FR Socket, USB	55	220-240	6800	4000	IP54	Type A + C 2.4 A Max	French
	IMT47276	Thorsman WL 4000 lm, 35 W, DK version, USB	35	220-240	4000	4000	IP54	Type A + C 2.4 A Max	Danish
	IMT47277	Thorsman WL 6800 lm, 55 W, DK version, USB	55	220-240	6800	4000	IP54	Type A + C 2.4 A Max	Danish
	IMT47278	Thorsman WL 8500 lm, 75 W, DK version, USB	75	220-240	8500	4000	IP54	Type A + C 2.4 A Max	Danish
	IMT47279	Thorsman WL Rechargeable 4000 lm, 35 W, USB	35	220-240	4000	4000	IP54	Type A + C 2.4 A Max	NA

Installation material

Chocs	Plug	Operation Temperature (°C)	CRI	PF	Beam angle	Lifetime (h)	Cable	Weight (g)	Dimensions (mm)	Energy Class (For Light Source)
IK08	Schuko Plug without earth	-25...+40	Ra>80	≥ 0.9	120°	>50000	3 m x H05RN-F 2 x 1.0 mm ²	1120	210 x 200 x 66.5	D
IK08	Hybrid E/F (CEE 7/7) Plug	-25...+40	Ra>80	≥ 0.9	120°	>50000	3 m H07RN-F 3 x 1.5 mm ²	2230	270 x 260 x 75	D
IK08	Hybrid E/F (CEE 7/7) Plug	-25...+40	Ra>80	≥ 0.9	120°	>50000	4.2 m H07RN-F 3 x 1.5mm ²	2700	290 x 280 x 82	D
IK08	Hybrid E/F (CEE 7/7) Plug	-25...+40	Ra>80	≥ 0.9	120°	>50000	5 m H07RN-F 3 x 1.5 mm ²	3600	350 x 340 x 82.5	D
IK08	Hybrid E/F (CEE 7/7) Plug	-25...+40	Ra>80	≥ 0.9	120°	>50000	3 m x H05RN-F 2 x 1.0 mm ²	2230	270 x 260 x 75	D
IK08	Hybrid E/F (CEE 7/7) Plug	-25...+40	Ra>80	≥ 0.9	120°	>50000	4.2 m H07RN-F 3 x 1.5 mm ²	2700	290 x 280 x 82	D
IK08	Danish	-25...+40	Ra>80	≥ 0.9	120°	>50000	3 m H07RN-F 3 x 1.5 mm ²	2230	270 x 260 x 75	D
IK08	Danish	-25...+40	Ra>80	≥ 0.9	120°	>50000	4.2 m H07RN-F 3 x 1.5 mm ²	2700	290 x 280 x 82	D
IK08	Danish	-25...+40	Ra>80	≥ 0.9	120°	>50000	5 m H07RN-F 3 x 1.5 mm ²	3600	350 x 340 x 82.5	D
IK08	Schuko Plug without earth	0...+40	Ra>80	≥ 0.9	120°	>50000	3 m x H05RN-F 2 x 1.0 mm ²	2420	270 x 260 x 105.7	D



22070883 - WORKLIGHT - SETUP - 1.495

LED Worklamps

Description

The Thorsman LED Worklamp range offers more features and covers a maximum number of applications, thanks to its different models. All products in the range are equipped with the latest LED technology, to offer greater energy efficiency, higher light quality, and a longer lifetime.

Application

The high IP and IK rating makes this worklamp ideal for harsh conditions both indoors and outdoors. The built-in light dimmer function makes it possible to adjust the light in five different steps according to the work task. A socket outlet on the back for extra power connectivity. The built-in Type A and Type C USB outlet to charge mobile devices. Cable management to store the power cable and helps to prevent cable damage. Patented suspension strap and the angle-adjustable handle make it easy to transport, carry, place, mount or hang. Perfect for professional craftsmen.

+ Benefits

- Ergonomic & easy to transport, position, and mount
- Carry a handle and strap
- 3 to 5-meter length power cable enhanced the flexibility at worksite
- Ideal for harsh conditions: designed and approved for heavy use, both indoors and outdoors
- Shock-absorbent rubber coating
- Efficient LED technology: ultra long-life
- 5-step dimming
- 2-port A+C USB charger
- A socket outlet for extra power connectivity
- Cable clip and cable management to store and protect the power cable when not used
- Long operation time from 2 hours up to 8 hours, depends on light level output (IMT47279)

Accessories

Description

The Thorsman Worklamp Tripod is designed to bring even more flexibility and better light distribution to projects and applications. This tripod can be placed on any surface by adjusting the three legs, the bracket can be fixed using a screw on top of the tripod. The Thorsman Tripod and Bracket are suitable for Thorsman worklamps.

Range



2-Pin Plug w/o Earth	Type	Plug	Power	Lumen	Cable	IP	Weight	Ref. No.
	Thorsman 18 W	2-Pin plug	18 W	2100 lm	3 m	IP65	1120	IMT47270







Schuko Socket	Type	Plug	Power	Lumen	Cable	IP	Weight	Ref. No.
	Thorsman 35 W	Hybrid E/F (CEE 7/7) Plug	35 W	4000 lm	3 m	IP54	2230	IMT47271
	Thorsman 55 W	Hybrid E/F (CEE 7/7) Plug	55 W	6800 lm	4 m	IP54	2700	IMT47272
	Thorsman 75 W	Hybrid E/F (CEE 7/7) Plug	75 W	8500 lm	5 m	IP54	3600	IMT47273



Range

French Socket	Type	Plug	Power	Lumen	Cable	IP	Weight	Ref. No.
	Thorsman 35 W	Hybrid E/F (CEE 7/7) Plug	35 W	4000 lm	3 m	IP54	2230	IMT47274
	Thorsman 55 W	Hybrid E/F (CEE 7/7) Plug	55 W	6800 lm	4 m	IP54	2700	IMT47275
								

Danish Socket	Type	Plug	Power	Lumen	Cable	IP	Weight	Ref. No.
	Thorsman 35 W	Danish plug	35 W	4000 lm	3 m	IP54	2230	IMT47276
	Thorsman 55 W	Danish plug	55 W	6800 lm	4 m	IP54	2700	IMT47277
	Thorsman 75 W	Danish plug	75 W	8500 lm	5 m	IP54	3600	IMT47278

Rechargeable 2-Pin Plug w/o Earth	Type	Plug	Power	Lumen	Cable	IP	Weight	Ref. No.
	Thorsman 35 W Rechargeable	2-Pin plug	35 W	4000 lm	3 m	IP54	2420	IMT47279
								

Accessories

Type	Ref. No.
 Thorsman Tripod and Bracket	IMT47281