

# PRODUCT DATASHEET SMART+ WiFi Classic 75 9.5 W/2700 K E27

SMART+ WiFi Classic Dimmable | Classic bulb shape with WiFi technology



#### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor applications only in suitable luminaires

#### **Product benefits**

- Wireless control via app
- Easy to install and use
- Contains no mercury

#### **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Network protocol: WiFi
- Dimmable
- Lifetime: up to 15,000 h




## **TECHNICAL DATA**

## Electrical data

Nominal wattage	9.5 W
Construction wattage	9.50 W
Nominal voltage	230 V
Nominal current	68 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.5
Claimed equiv. conventional lamp power	75 W

#### Photometrical data

Light color (designation)	Warm White
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	1055 lm
Luminous flux	1055 lm
Luminous efficacy	111 lm/W
Color temperature	2700 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9



# Light technical data

Beam angle	215 °
Starting time	< 0.5 s

# **Dimensions & Weight**



Product weight	50.00 g
Diameter	60.00 mm
Length	115.00 mm
Width	60.00 mm
Height	60.00 mm
Outer bulb [PICOS]	A60

## Lifespan

Lifespan	15000 h
Lumen maintenance at end of serv	0.70

## Colors & materials

Housing color	White
	***************************************

# Temperatures & operating conditions

## Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E27

# **Capabilities**

Dimmable	Yes
Compatible smart home technology	Google Assistant / Amazon Alexa

#### Certificates & Standards

Energy efficiency class	F <sup>1)</sup>
Energy consumption	10.00 kWh/1000h
Standards	CE
Type of protection	IP20

 $<sup>1) \ {\</sup>sf Energy \ efficiency \ class \ (EEC) \ on \ a \ scale \ of \ A \ (highest \ efficiency) \ to \ G \ (lowest \ efficiency)}$ 

## Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
--------------------------	-----



Mains or non-mains Light source cap-type (or other electric interface) E27 Connected light source (CLS) yes Color-tuneable light source No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Standby power 0.50 Networked standby power for CLS 0.50 Claim of equivalent power Yes Chromaticity coordinate x 0.463 Chromaticity coordinate y 0.420 R9 Colour rendering index Beam angle correspondence SPHERE_360 Survival factor 0.9 Displacement factor LED light source replaces a fluorescent light source No EPREL ID  No	Non-directional or directional	NDLS
Light source cap-type (or other electric interface)  E27  Connected light source (CLS)  yes  Color-tuneable light source  No  High luminance light source  No  Anti-glare shield  No  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.50  Networked standby power for CLS  Claim of equivalent power  Yes  Chromaticity coordinate x  Chromaticity coordinate y  R9 Colour rendering index  Beam angle correspondence  SPHERE_360  Survival factor  0.50  LED light source replaces a fluorescent light source  No		
Connected light source (CLS)  Color-tuneable light source  No  Envelope  No  High luminance light source  No  Anti-glare shield  No  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.50  Networked standby power for CLS  Claim of equivalent power  Yes  Chromaticity coordinate x  Chromaticity coordinate y  R9 Colour rendering index  Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  LED light source replaces a fluorescent light source  No	Mains or non-mains	MLS
Color-tuneable light source  No  High luminance light source  No  Anti-glare shield  No  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.50  Networked standby power for CLS  Claim of equivalent power  Yes  Chromaticity coordinate x  Chromaticity coordinate y  R9 Colour rendering index  Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  No	Light source cap-type (or other electric interface)	E27
Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Standby power 0.50 Networked standby power for CLS 0.50 Claim of equivalent power Yes Chromaticity coordinate x 0.463 Chromaticity coordinate y 0.420 R9 Colour rendering index 0.00 Beam angle correspondence SPHERE_360 Survival factor 0,9 Displacement factor 0.50 LED light source replaces a fluorescent light source No	Connected light source (CLS)	yes
High luminance light source  Anti-glare shield  No  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.50  Networked standby power for CLS  Claim of equivalent power  Yes  Chromaticity coordinate x  0.463  Chromaticity coordinate y  R9 Colour rendering index  0.00  Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  0.50  LED light source replaces a fluorescent light source	Color-tuneable light source	No
Anti-glare shield  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.50  Networked standby power for CLS  Claim of equivalent power  Yes  Chromaticity coordinate x  0.463  Chromaticity coordinate y  R9 Colour rendering index  Beam angle correspondence  SPHERE_360  Survival factor  0.99  Displacement factor  0.50  No	Envelope	No
Correlated colour temperature type  SINGLE_VALUE  Standby power  0.50  Networked standby power for CLS  0.50  Claim of equivalent power  Yes  Chromaticity coordinate x  0.463  Chromaticity coordinate y  0.420  R9 Colour rendering index  0.00  Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  0.50  LED light source replaces a fluorescent light source  No	High luminance light source	No
Standby power       0.50         Networked standby power for CLS       0.50         Claim of equivalent power       Yes         Chromaticity coordinate x       0.463         Chromaticity coordinate y       0.420         R9 Colour rendering index       0.00         Beam angle correspondence       SPHERE_360         Survival factor       0,9         Displacement factor       0.50         LED light source replaces a fluorescent light source       No	Anti-glare shield	No
Networked standby power for CLS  Claim of equivalent power  Yes  Chromaticity coordinate x  0.463  Chromaticity coordinate y  0.420  R9 Colour rendering index  0.00  Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  0.50  LED light source replaces a fluorescent light source  No	Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power  Chromaticity coordinate x  0.463  Chromaticity coordinate y  0.420  R9 Colour rendering index  0.00  Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  0.50  LED light source replaces a fluorescent light source  No	Standby power	0.50
Chromaticity coordinate x  Chromaticity coordinate y  R9 Colour rendering index  0.00  Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  0.50  LED light source replaces a fluorescent light source  No	Networked standby power for CLS	0.50
Chromaticity coordinate y  R9 Colour rendering index  0.00  Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  0.50  LED light source replaces a fluorescent light source  No	Claim of equivalent power	Yes
R9 Colour rendering index  Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  0.50  LED light source replaces a fluorescent light source  No	Chromaticity coordinate x	0.463
Beam angle correspondence  SPHERE_360  Survival factor  0,9  Displacement factor  0.50  LED light source replaces a fluorescent light source  No	Chromaticity coordinate y	0.420
Survival factor     0,9       Displacement factor     0.50       LED light source replaces a fluorescent light source     No	R9 Colour rendering index	0.00
Displacement factor 0.50  LED light source replaces a fluorescent light source No	Beam angle correspondence	SPHERE_360
LED light source replaces a fluorescent light source  No	Survival factor	0,9
	Displacement factor	0.50
EPREL ID 1403132,528200	LED light source replaces a fluorescent light source	No
	EPREL ID	1403132,528200
Model number AC33913,AC27507	Model number	AC33913,AC27507

#### **DOWNLOAD DATA**

	DOWNLOAD DATA
PDF	Declarations Of Conformity CE
PDF	Declarations Of Conformity CE
PDF	Installation guide

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075485419	Folding box 1	61 mm x 96 mm x 154 mm	124.00 g	0.90 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075485426	Shipping box 4	210 mm x 165 mm x 135 mm	629.00 g	4.68 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

