




BOX_L

LED outdoor surface-mounted wall and ceiling light, anthracite, IP44, 3000K, 19W

The single-headed BOX-L LED wall light consists of painted aluminium and frosted acrylic, which covers the three light outlets. It is protection class IP44 and suitable for outdoor use. The electrical connection of the luminaire, which comes in various colours, is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.	1002035
IP Code	IP 54
Impact resistance class	IK 05
Impact resistance	0.7 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	19 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	17 A
Duration of inrush current	35 µs
Stroboscopic effect (SVM)	0.01
Lumen	600 lm
Colour temperature	3000 Kelvin
Color	anthracite
LXXBXX data	L70B50
Service life	30000 h
Width	25 cm
Height	11 cm

Light Source

916326	 An energy label icon consisting of a yellow arrow pointing right, with the letters 'A', 'G', and 'E' stacked vertically inside it.
--------	--

Depth	11 cm
Net weight	1.265 kg
Gross weight	1.4 kg
BIG WHITE Page	686