

# Nexus Linesman

## DESCRIPTION

Modern, recreational styled Safety Helmet with 'Micro Peak' for optimum visibility. Includes 4 point quick release harness for added stability and comfort with non-vented shell for improved electrical resistance.

## SPECIFICATION

Product Codes and Helmet Options	Code	Option	Weight
	S16E*RL	Ratchet	386gm
	S16E*L	Non Ratchet	365gm
Size	51 - 63cm		
Peak	Micro (20mm)		

\*Insert colour code of helmet.

## MATERIALS

Shell	ABS (Acrylonitrile-Butadiene-Styrene)
Cradle	6 Point Terylene webbing
Headband	LDPE (Low Density Polyethylene)
Sweatband	Dry-Tech (Polyester)
Ratchet	Acetal with 3mm foam backing
EN 397 Harness	Printed Polyester and Acetal Clips




## COLOURS


	White	Blue	Red	Yellow	Orange	Green	Light Blue	Black	Grey	High-Vis Yellow	High-Vis Orange
Colour Code	W	B	R	Y	O	G	LB	K	E	HVY	HVO
RAL	9010	5026	3031	1018	2003	6036	5005	9005	7039	1026	2005
Pantone	White	2768	1807	109	1505	343	2935	Black	405	809	1655

Please note: the closest matching RAL colours are listed.


## CORPORATE BADGING



Front	
↔	75mm
↕	40mm



Sides	
↔	50mm
↕	40mm



Rear	
↔	50mm
↕	50mm

## EUROPEAN AND INTERNATIONAL STANDARDS WITH OPTIONS

Product	EN 397:2012 + A1:2012	OPTIONS WITHIN EN 397				OPTIONS ADDITIONAL TO EN 397		EN 50365 (1000V a.c.) For use on low voltage insulations	ANSI/ISEA Z89.1-2009 Type 1		Tested to AS/NZS 1801:1997 Type 1	
		Lateral Deformation (LD)	-30°C (Low Temperature)	Molten Metal (MM)	440V a.c. (Electrical Resistance)	1000V a.c. (Electrical Resistance)	-40°C (Low Temperature)		Class C (Conductive 0V a.c.)	Class E (20,000V a.c.)	Class C (Conductive 0V a.c.)	Class E (20,000V a.c.)
Non-vented with Ratchet S16E*RL	✓	✓	✓	✓	✓	✓	✓	✓		✓		✓
Non-vented without Ratchet S16E*L	✓	✓	✓	✓	✓	✓	✓	✓		✓		✓

## ACCESSORIES

Face	Compatible with  range of Face Protection (carriers and face screens)
Accessory Clips	 Clip Sets for fitting safety helmet accessories S565
Ear	Compatible with Centurion helmet mounted Aegean S42E and Baltic S41E Ear Defenders (supplied with S565  accessory clips)
Eye	Clear S589 or Smoke Grey S589SE moulded Polycarbonate Eye Shield with anti scratch/fog coating
Stickers	High Intensity Reflective Sticker sets available in a range of colours S30NHRS
Linesman Harness	S30LY 4 point quick release EN 397 Black Harness
Sweatband	S31D Dry-Tech sweatband
Standard Cradle	S33/S34 Terylene Cradle with Dry-Tech Sweatband
Ratchet Cradle	S33/35 Terylene Cradle with Premium 'Twist2Fit' Ratchet and Dry-Tech Sweatband

## PACKAGING AND MAINTENANCE

Packaging	5 per colour, box size 28 x 22 x 50cm, Box Weight 2.34kg (S16E* L), 2.44kg (S16E* RL)
Storage	Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C) May be stored in the dark for up to 5 years Do not store in direct/high heat or sunlight as this may distort the shell
Lifetime	The Centurion helmet has an in-use life of up to 5 years Excessive wear and tear can considerably reduce the lifespan of the product
Cleaning	Clean using warm soapy water and soft cloth
Disposal	Recycling is preferred when possible. Look out for the recycling symbol for material category