## SIEMENS

## Data sheet

## 5TT5830-0



INSTA contactor with 4 NO contacts Contact for 230 V AC, 400 V 25 A Control 230 V AC

Model					
product brand name	SENTRON				
product designation	Insta contactor				
design of the product	4 NO contacts				
type of voltage of the operating voltage	AC				
type of voltage of the operating voltage for actuation	AC				
Supply voltage					
operating voltage rated value					
• minimum	440 V				
• maximum	440 V				
Protection class					
protection class IP	IP20				
Switching capacity					
switching capacity active power with incandescent lamp load	2 000 W				
Dissipation					
power loss [W] for rated value of the current at AC in hot operating state per pole	2.2 W				
Control current					
control supply voltage					
rated value	230 V				
rated value maximum	230 V				
Product details					
product component slide for manual operation	No				
number of NC contacts	0				
number of NO contacts	4				
product extension installable supplementary devices	Yes				
Connections					
installation or assembly note	provision must be made for spacers to ensure heat dissipation				
Mechanical Design					
height	90 mm				
width	36 mm				
depth	71 mm				
installation depth	0 mm				
number of modular width units	2				
net weight	258 g				
General Product Approval		Declaration of Con- formity			

	<u>Confirmation</u>	<u>Miscellaneous</u>	<u>Miscellaneous</u>	EAC	CE EG-Konf.
Declaration of Con- formity	Test Certificates	other		Environment	
UK CA	<u>Special Test Certific-</u> <u>ate</u>	<u>Confirmation</u>	<u>Miscellaneous</u>	Environmental Con- firmations	
https://press.siemens.cd Siemens is working of Please contact your loc EAC relevant market (o Information on the par https://support.industry. Information- and Down http://www.siemens.com Industry Mall (Online of https://mall.industry.sier Service&Support (Mar https://support.industry. Image database (prod	ther than the sanctioned I ckaging siemens.com/cs/ww/en/vi nloadcenter (Catalogs, I n/lowvoltage/catalogs ordering system) mens.com/mall/en/en/Cat isemens.com/mall/en/en/Cat siemens.com/cs/ww/en/p uct images, 2D dimensi- siemens.com/bilddb/cax_o	e/siemens-wind-down-rus rent EAC certificates. status of validity of the E/ EAEU member states Ru iew/109813875 Brochures,) alog/product?mlfb=5TT5: acteristics, FAQs,) s/5TT5830-0 on drawings, 3D model en.aspx?mlfb=5TT5830-0	AC certification if you intend Issia or Belarus). 830-0 s, device circuit diagrams	63.9	these products to an
G					

6.8

last modified:

7/30/2022 🖸