

PRODUCT DATASHEET HALOSTAR ST 10 W 12 V G4

HALOSTAR® STAR | Low-voltage halogen lamps with pin base



Areas of application

- Kitchen lighting
- Mirror lighting
- Lighting for reading
- Entrance lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

Product benefits

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter

Product features

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index R_a : 100
- Base: G4, GY6.35




TECHNICAL DATA

Electrical data

| | |
|----------------------|---------|
| Nominal wattage | 10 W |
| Construction wattage | 10.00 W |
| Nominal voltage | 12 V |

Photometrical data

| | |
|---------------------------|------------|
| Luminous flux | 130 lm |
| Luminous efficacy | 13 lm/W |
| Light color (designation) | Warm White |
| Color temperature | 2800 K |
| Color rendering index Ra | 100 |
| Light color | 1028 |
| UV protection | Yes |



Light technical data

| | |
|---------------|-------|
| Starting time | 0.0 s |
|---------------|-------|

Dimensions & Weight

| | |
|---------------------------|----------|
| Overall length | 33.00 mm |
| Light center length (LCL) | 22,0 mm |
| Diameter | 10.00 mm |
| Product weight | 1.17 g |

Lifespan

| | |
|----------------------------|-------|
| Number of switching cycles | 50000 |
|----------------------------|-------|

Additional product data

| | |
|-----------------------------|-----|
| Base (standard designation) | G4 |
| Mercury-free | Yes |

Capabilities

| | |
|------------------|-----|
| Dimmable | Yes |
| Burning position | Any |

Certificates & Standards

| | |
|-------------------------|-----------------|
| Energy efficiency class | G |
| Energy consumption | 10.00 kWh/1000h |

Country-specific categorizations

| | |
|-----------------|-------------------------|
| ILCOS | HSGST/UB-10-12-G4-10/22 |
| Order reference | 64415 ST |

Energy labelling regulation data acc EU 2019/2015

| | |
|---|--------------|
| Lighting technology used | OTHER |
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | G4 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 33.00 mm |
| Height | 10.00 mm |
| Width | 10.00 mm |
| Chromaticity coordinate x | 0.452 |
| Chromaticity coordinate y | 0.409 |
| Beam angle correspondence | SPHERE_360 |
| EPREL ID | 714476 |
| Model number | AC35298 |

DOWNLOAD DATA

Documents and certificates

Declarations Of Conformity CE

Photometric and lighting design files

Spectral power distribution

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4008321201812 | Blister 2 | 140 mm x 14 mm x 79 mm | 24.70 g | 0.15 dm ³ |
| 4008321201829 | Shipping box 20 | 164 mm x 130 mm x 148 mm | 202.70 g | 3.16 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.