Product fiche

Supplier name or trademark	GENVEX
Model identifier	ECO375.2 PET
Specific energy consumption (cold zone)	- kWh/(m² x a)
Specific energy consumption class (average zone)	А
Specific energy consumption (average zone)	39,2 kWh/(m² x a)
Specific energy consumption (warm zone)	- kWh/(m² x a)
Гуроlоду	Bidirectional Ventilation Unit (BVU)
Type of drive	Variable speed drive
Type of heat recovery system	Recuperative
Thermal efficiency of heat recovery	85,0 %
Maximum flow rate	450 m³∕h
Electric power input of the fan drive	166,0 W
Sound power level	48 dB
Reference flow rate	0,087 m³/s
Reference pressure difference	50 Pa
Specific Power Input	0,24 W/(m³/h)
Control factor	0,85
Control typology	Central demand control - 0,85
Maximum internal leakage rates	2,0 %
Maximum external leakage rates	0,7 %
Position of visual filter warning	DISPLAY
Description of visual filter warning	AFTER A SPECIFIC TIME THE DISPLAY WIL
	L TELL THAT IT IS TIME TO CLEAN THE FILT
	ERS OR REPLACE THEM WITH NEW ONES.
Pre-/dis-assembly instructions URL	http://www.genvex.com
Annual Electricity Consumption	258,0 kWh electricity/annum
Annual Heating Saved at cold climate	8 792,0 kWh primary energy/annum
Annual Heating Saved at average climate	4 494,0 kWh primary energy/annum
Annual Heating Saved at warm climate	2 032,0 kWh primary energy/annum