# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Ansell Lighting

**Supplier's address:** ANSELL (WARRINGTON), Ansell Electrical Products Ltd Unit 6B Stonecross Ind. Park Yew Tree Way Warrington Cheshire WA3 3JD

**Model identifier:** P/24/04/20/05/00/S05/01

**Type of light source:**

| | | | |
|---|---|---|---|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | Connector | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | Yes | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Yes |

**Product parameters**

| Parameter | Value | Parameter | Value |
|---|---|---|---|
| **General product parameters:** | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 900 | Energy efficiency class | G |
| Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º) | 14 500 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2700...6500 |
| On-mode power ($P_{on}$), expressed in W | 900,0 | Standby power ($P_{sb}$), expressed in W and rounded to the second decimal | - |
| Networked standby power ($P_{net}$) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 92 |
| Outer dimensions without separate control gear, light- | Height: 50 000 | Spectral power distribution in the range 250 nm to 800 nm, at full-load | See image in last page |
| | Width: 12 | | |
| | Depth: 2 | | |

| | | | | |
|---|---|---|---|---|
| ing control parts and non-lighting control parts, if any (millimetre) | | | | |
| Claim of equivalent power[a] | | - | If yes, equivalent power (W) | - |
| | | | Chromaticity coordinates (x and y) | 0,310<br>0,329 |
| **Parameters for LED and OLED light sources:** | | | | |
| R9 colour rendering index value | | 60 | Survival factor | 0,90 |
| the lumen maintenance factor | | 0,96 | | |

[a] '-' : not applicable;

[b] '-' : not applicable;


Spectrum
1.2
1.0
0.8
0.6
0.4
0.2
0.0
380
480
580
680
780
Wavelength(nm)

Model placed on the Union market from 01/09/2023

**EPREL registration number:** 1753358

https://eprel.ec.europa.eu/qr/1753358

**Supplier:** Ansell (Sales & Distribution) Republic of Ireland Limited (Manufacturer)

**Website:** http://www.anselluk.com/

**Customer care service:**

**Name:** ANSELL (WARRINGTON)

**Website:** http://www.anselluk.com/

**Email:** saleswarrington@anselluk.com

**Phone:** 01942 433333

**Address:**
Ansell Electrical Products Ltd
Unit 6B Stonecross Ind. Park
Yew Tree Way
Warrington
Cheshire
WA3 3JD