

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Dansani

Supplier's address: Dansani, Finlandsvej 8, 6100 Haderslev, DK

Model identifier: 190304708 LED 04.2023

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	No cap-type		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters


Parameter		Value	Parameter	Value
General product parameters:				
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer		7	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		948 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2100...6500
On-mode power (P_{on}), expressed in W		7,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	92
Outer dimensions without separate control gear, light-	Height	760	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	10		
	Depth	3		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,311 0,328	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	75	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a) '-': not applicable;

(b) '-': not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.3110$ $y=0.3284$ $u'=0.1969$ $v'=0.4678$
 CCT=6601K(Duv=0.0037) Dominant WL:Ld =488.9nm Purity=7.9%
 Ratio:R=14.9% G=77.8% B=7.3% Peak WL:Lp=456.1nm FWHM=25.9nm
 Render Index:Ra=92.5
 R1 =94 R2 =100 R3 =97 R4 =87 R5 =91 R6 =94 R7 =90
 R8 =87 R9 =75 R10=97 R11=89 R12=65 R13=97 R14=99 R15=91

Photo Parameters:

Flux = 948.9 lm Eff. : 135.52 lm/W Fe = 3.397 W

Electrical parameters:


V = 12.000 V I = 0.5835 A P = 7.002 W PF = 1.000

LEVEL:OUT WHITE:ANSI_6500K

Status: Integral T = 783 ms Ip = 51775 (79%)

Model:LPP-080MW-6500K-LED(84PCS)	Number:1
Tester:ZW	Date:2021-09-27
Temperature:25.3Deg	Humidity:65.0%
Manufacturer:GB	Remarks:SE001131

Model placed on the Union market from 01/04/2023



EPREL registration number: 1654137

<https://eprel.ec.europa.eu/qr/1654137>

Supplier: Dansani A/S (Manufacturer)

Website:

Customer care service:

Name: Dansani

Website: www.dansani.dk

Email: sba@dansani.dk

Phone: +4523829794

Address:

Finlandsvej 8
6100 Haderslev
Denmark