

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Dansani

Supplier's address: Dansani, Finlandsvej 8, 6100 Haderslev, DK

Model identifier: 190303821 LED 09.2022

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	No cap-type		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	9	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 098 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 146
On-mode power (P_{on}), expressed in W	9,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	98
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,422 0,247	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	98	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a) : not applicable;

(b) : not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4220$ $y=0.3894$ $u'=0.2472$ $v'=0.5132$
 CCT=3146K(Duv=-0.0038) Dominant WL:Ld =583.8nm Purity=43.5%
 Ratio:R=24.3% G=72.5% B=3.2% Peak WL:Lp=635.5nm FWHM=177.3nm
 Render Index:Ra=97.9
 R1 =99 R2 =99 R3 =96 R4 =97 R5 =99 R6 =96 R7 =98
 R8 =99 R9 =98 R10=97 R11=96 R12=82 R13=99 R14=97 R15=98

Photo Parameters:

Flux = 1098 lm Eff. : 122.55 lm/W Fe = 3.239 W

Electrical parameters:


V = 25.606 V I = 0.3500 A P = 8.962 W PF = 1.000

LEVEL:OUT WHITE:ANSI_3000K

Status: Integral T = 963 ms Ip = 58467 (89%)

Model:LPC32-60DL-3150K-LED(98PCS) Number:4
 Tester:ZW Date:2022-01-07
 Temperature:25.3Deg Humidity:65.0%
 Manufacturer:GB Remarks:SE001497

Model placed on the Union market from 01/09/2022



EPREL registration number: 1279096

<https://eprel.ec.europa.eu/qr/1279096>

Supplier: Dansani A/S (Manufacturer)

Website:

Customer care service:

Name: Dansani

Website: www.dansani.dk

Email: sba@dansani.dk

Phone: +4523829794

Address:

Finlandsvej 8
6100 Haderslev
Denmark